

Miyano

BNE 65 MYY/SY



High-tech from heimatec - heimatec - Tools and systems for productive turning and milling

heimatec belongs to the international technology and quality leaders for precision tools and specializes in the development and production of high-precision static and live tools for all CNC lathes, CNC turn-/mill machines and CNC machining centers.

The range of products* spans from static BMT and VDI tool holders, live tools up to highly complex customer-specific individual solutions. heimatec, headquartered in Renchen, has a own subsidiary in Asia and India and numerous representatives as well as trading partners all over the world.

*OUR PRODCUTS

Static tool holders

Live tool units

Precision tools

Tools for turning and machining centres

Tools for swiss type lathes

Tool changing and uick-change systems

Tool systems for gear production

Digital tool management

This catalogue, including all its parts, is protected by copyright. Any use outside the restricted limitations of the Copyright Act without the consent of heimatec is inadmissible and liable to prosecution. This applies in particular to duplication, translation, microfilming and storage and processing in electronic systems.

heimatec GmbH reserves the right to make technical changes at any time without giving prior notice. This applies in particular to adjustments at any time to meet new or changed international standards, or in case of further developments of our products or manufacturing processes.

The current version of our General Terms and Conditions can be found on our website.

| Part-# | Name |
|--------|------|
|--------|------|

8 010 45 047

Axial drilling and milling head ER 25 M



Weight [kg]: 1.740
 Tool drive: Flat (~DIN 1809)
 Shank size [mm]: 45.00
 Tool adaption: ER 25 M
 Gear ratio [i]: 1:1
 Torque max [Nm]: 50
 Rotation max [1/min]: 6000
 Rotating direction: same
 Coolant: EXT

8 010 45 050

Axial drilling and milling head ER 25 M IC



Weight [kg]: 2.000
 Tool drive: Flat (~DIN 1809)
 Shank size [mm]: 45.00
 Shank type: BMT
 Tool adaption: ER 25
 Gear ratio [i]: 1:1
 Torque max [Nm]: 50
 Rotation max [1/min]: 6000
 Rotating direction: same
 Coolant: IC/Ext
 Pressure max [bar]: 25

8 010 45 061

Axial drilling and milling head ER 25




Weight [kg]: 1.780
 Tool drive: Flat (~DIN 1809)
 Shank size [mm]: 45.00
 Shank type: BMT
 Tool adaption: ER 25
 Gear ratio [i]: 1:1
 Torque max [Nm]: 50
 Rotation max [1/min]: 6000
 Rotating direction: same
 Coolant: EXT


8 010 45 096

Axial drilling and milling head ER 25 AX UT IC



Weight [kg]: 2.000
 Tool drive: Flat (~DIN 1809)
 Shank size [mm]: 45.00
 Shank type: BMT
 Tool adaption: ER 25 A - u-tec
 Gear ratio [i]: 1:1
 Torque max [Nm]: 50
 Rotation max [1/min]: 6000
 Rotating direction: same
 Coolant: IC/Ext
 Pressure max [bar]: 25
 Please note: Combi bearing


| Part-# | Name | |
|---|--|--|
| 8 010 45 103 | Axial milling and drill holder ER 25 AX UT | |
|  | Weight [kg]: | 1.870 |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Please note: | Combi bearing |
| 8 010 45 181 | Axial drilling and milling head C 3 IC | |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | heimatec Capto(TM) C 3 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 25 |
| | Rotation max [1/min]: | 8000 |
| | Rotating direction: | same |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 100 |
| | Please note: | Check applicability; tool length check ! |
| 8 010 45 183 | Axial drilling and milling head C 3 | |
|  | Weight [kg]: | 3.800 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | heimatec Capto(TM) C 3 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 32 |
| | Rotation max [1/min]: | 8000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Please note: | Check applicability; tool length check ! |
| 8 010 45 224 | Axial drilling and milling head ER 25 AX UT | |
|  | Weight [kg]: | 1.900 |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 15000 |
| | Rotating direction: | same |
| | Coolant: | EXT |

| Part-# | Name | | |
|---|--|---|------------------|
|  | 8 010 45 225 | Axial drilling and milling head ER 25 AX UT IC | |
| | | Weight [kg]: | 2.100 |
| | | Tool drive: | Flat (~DIN 1809) |
| | | Shank size [mm]: | 45.00 |
| | | Shank type: | BMT |
| | | Tool adaption: | ER 25 A - u-tec |
| | | Gear ratio [i]: | 1:1 |
| | | Torque max [Nm]: | 50 |
| | | Rotation max [1/min]: | 12000 |
| | | Rotating direction: | same |
| | | Coolant: | IC/Ext |
| | | Pressure max [bar]: | 100 |
| | | Please note: | Dryrun possible |
| | 8 010 46 092 | Axial drilling and milling head HT 4 | |
| | | Weight [kg]: | 1.700 |
| | | Tool drive: | Flat (~DIN 1809) |
| | | Shank size [mm]: | 45.00 |
| | | Shank type: | BMT |
| | | Tool adaption: | HT 4 |
| | | Gear ratio [i]: | 1:1 |
| | | Torque max [Nm]: | 50 |
| | | Rotation max [1/min]: | 6000 |
| | | Rotating direction: | same |
| | Coolant: | EXT | |
| 8 010 46 112 | Axial drilling and milling head HT 4 IC | | |
| | | Weight [kg]: | 1.980 |
| | | Tool drive: | Flat (~DIN 1809) |
| | | Shank size [mm]: | 45.00 |
| | | Shank type: | BMT |
| | | Tool adaption: | HT 4 |
| | | Gear ratio [i]: | 1:1 |
| | | Torque max [Nm]: | 50 |
| | | Rotation max [1/min]: | 6000 |
| | | Rotating direction: | same |
| | Coolant: | IC/Ext | |
| | Pressure max [bar]: | 25 | |
| 8 010 46 206 | Axial drilling and milling head ER 32 AX UT | | |
| | | Weight [kg]: | 2.110 |
| | | Version: | Special |
| | | Tool drive: | Flat (~DIN 1809) |
| | | Shank size [mm]: | 45.00 |
| | | Shank type: | BMT |
| | | Tool adaption: | ER 32 A - u-tec |
| | | Gear ratio [i]: | 1:1 |
| | | Torque max [Nm]: | 50 |
| | | Rotation max [1/min]: | 6000 |
| | | Rotating direction: | same |
| | Coolant: | EXT | |
| | Please note: | stronger bearing | |


| Part-# | Name | |
|---------------------|--|---|
| 8 011 44 010 | Axial milling head universal arbor 16 |  |
| | | <p>Weight [kg]: 1.820 Tool drive: Flat (~DIN 1809) Shank size [mm]: 45.00 Shank type: BMT Tool adaption: Universal arbor 16 Gear ratio [i]: 1:1 Torque max [Nm]: 50 Rotation max [1/min]: 6000 Rotating direction: same Coolant: EXT Please note: Taper roller bearings</p> |
| 8 011 44 021 | Axial milling head universal arbor 3/4" | |
| | | <p>Weight [kg]: 1.840 Tool drive: Flat (~DIN 1809) Shank size [mm]: 45.00 Shank type: BMT Tool adaption: Universal arbor 3/4" (19,05mm) Gear ratio [i]: 1:1 Torque max [Nm]: 50 Rotation max [1/min]: 6000 Rotating direction: same Coolant: EXT Please note: Taper roller bearings</p> |
| 8 011 45 018 | Axial milling head universal arbor 22 |  |
| | | <p>Weight [kg]: 1.940 Tool drive: Flat (~DIN 1809) Shank size [mm]: 45.00 Shank type: BMT Tool adaption: Universal arbor 22 Gear ratio [i]: 1:1 Torque max [Nm]: 50 Rotation max [1/min]: 6000 Rotating direction: same Coolant: EXT Please note: Taper roller bearings</p> |
| 8 013 44 022 | Axial drilling and milling head ER 16 AX UT | |
| | <p>Weight [kg]: 2.350 Tool drive: Flat (~DIN 1809) Shank size [mm]: 45.00 Shank type: BMT Tool adaption: ER 16 A - u-tec Gear ratio [i]: 1:4 Torque max [Nm]: 5 Rotation max [1/min]: 24000 Rotating direction: same Coolant: EXT</p> | |

| Part-# | Name | |
|---|---|------------------|
| 8 013 44 023 | Axial drilling and milling head ER 16 AX UT IC | |
|  | Weight [kg]: | 2.450 |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:4 |
| | Torque max [Nm]: | 5 |
| | Rotation max [1/min]: | 24000 |
| | Rotating direction: | same |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 100 |
| | Please note: | Dryrun possible |
| 8 019 44 012 | Axial drilling and milling head ER 20 | |
|  | Weight [kg]: | 4.020 |
| | Notation: | offset |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 20 |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 12 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| 8 019 44 019 | Axial drilling and milling head ER 16 AX UT | |
| | Weight [kg]: | 4.260 |
| | Notation: | offset |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 12 |
| | Rotation max [1/min]: | 10000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Please note: | stronger bearing |
| 8 019 44 020 | Axial drilling and milling head ER 16 M | |
| | Weight [kg]: | 3.960 |
| | Notation: | offset |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 |
| | Gear ratio [i]: | 1:3 |
| | Torque max [Nm]: | 10 |
| | Rotation max [1/min]: | 15000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Offset [mm]: | 34,5 |

| Part-# | Name | |
|---------------------|---|-------------------------|
| 8 019 44 060 | Axial drilling and milling head ER 20 | |
| | Weight [kg]: | 4.000 |
| | Notation: | offset |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 20 |
| | Gear ratio [i]: | 1:3 |
| | Torque max [Nm]: | 10 |
| | Rotation max [1/min]: | 15000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Offset [mm]: | 34,5 |
| 8 019 44 073 | Axial drilling and milling head ER 20 AX UT IC | |
| | Weight [kg]: | 4.910 |
| | Notation: | offset; 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 20 A - u-tec |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 16 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | opposite |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | stronger bearing |
| | Offset [mm]: | 34,5 |
| 8 019 44 078 | Axial drilling and milling head ER 16 AX UT | |
| | Weight [kg]: | 3.890 |
| | Notation: | offset |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:3 |
| | Torque max [Nm]: | 10 |
| | Rotation max [1/min]: | 15000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Offset [mm]: | 34,5 |
| 8 019 44 114 | Axial drilling and milling head ER 20 AX UT | |
| | Notation: | offset; 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 20 A - u-tec |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 16 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Please note: | stronger bearing |
| | Offset [mm]: | 34,5 |

| Part-# | Name | |
|---|--|-------------------------|
| 8 019 45 093 | Axial drilling and milling head ER 25 AX UT IC | |
| | Weight [kg]: | 5.860 |
| | Notation: | offset; 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 2:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 3000 |
| | Rotating direction: | same |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | stronger bearing |
| | Offset [mm]: | 69 |
| 8 019 45 102 | Axial drilling and milling head ER 25 AX UT | |
| | Weight [kg]: | 5.400 |
| | Notation: | offset; 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 2:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 3000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Please note: | stronger bearing |
| | Offset [mm]: | 69 |
| 8 030 44 082 | Radial drilling and milling head ER 16 AX UT | |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:4 |
| | Torque max [Nm]: | 5 |
| | Rotation max [1/min]: | 24000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Center distance [mm]: | 65 |
| 8 030 44 099 | Radial drilling and milling head ER 16 AX UT IC | |
|  | Weight [kg]: | 4.900 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:4 |
| | Torque max [Nm]: | 5 |
| | Rotation max [1/min]: | 24000 |
| | Rotating direction: | opposite |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Center distance [mm]: | 65 |

| Part-# | Name | |
|---------------------|--|------------------|
| 8 030 44 109 | Radial drilling and milling head ER 20 AX UT IC | |
| | Weight [kg]: | 5.950 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 20 A - u-tec |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 16 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | stronger bearing |
| | Center distance [mm]: | 77 |
| 8 030 45 096 | Radial drilling and milling head ER 25 | |
| | Weight [kg]: | 5.190 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 12 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Center distance [mm]: | 65 |
| 8 030 45 101 | Radial drilling and milling head ER 25 IC | |
| | Weight [kg]: | 5.450 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 12 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | opposite |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Center distance [mm]: | 65 |
| 8 030 45 120 | Radial drilling and milling head ER 25 | |
| | Weight [kg]: | 5.400 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Center distance [mm]: | 65 |



| Part-# | Name |
|--------|------|
|--------|------|

| | |
|-----------------------|--|
| 8 030 45 121 | Radial drilling and milling head ER 25 IC |
| Weight [kg]: | 5.570 |
| Notation: | 180° reversible |
| Tool drive: | Flat (~DIN 1809) |
| Shank size [mm]: | 45.00 |
| Shank type: | BMT |
| Tool adaption: | ER 25 |
| Gear ratio [i]: | 1:1 |
| Torque max [Nm]: | 50 |
| Rotation max [1/min]: | 12000 |
| Rotating direction: | opposite |
| Coolant: | IC/Ext |
| Pressure max [bar]: | 140 |
| Please note: | strong version |
| Center distance [mm]: | 65 |



| | |
|-----------------------|--|
| 8 030 45 136 | Radial drilling and milling head ER 25 AX UT IC |
| Weight [kg]: | 5.370 |
| Notation: | 180° reversible |
| Tool drive: | Flat (~DIN 1809) |
| Shank size [mm]: | 45.00 |
| Shank type: | BMT |
| Tool adaption: | ER 25 A - u-tec |
| Gear ratio [i]: | 1:1 |
| Torque max [Nm]: | 50 |
| Rotation max [1/min]: | 12000 |
| Rotating direction: | opposite |
| Coolant: | IC/Ext |
| Pressure max [bar]: | 140 |
| Center distance [mm]: | 65 |



| | |
|-----------------------|---|
| 8 030 45 163 | Angle-mill- and drill holder ER 25 AX UT |
| Weight [kg]: | 5.700 |
| Notation: | 180° reversible |
| Tool drive: | Flat (~DIN 1809) |
| Shank size [mm]: | 45.00 |
| Tool adaption: | ER 25 A - u-tec |
| Gear ratio [i]: | 1:1 |
| Torque max [Nm]: | 50 |
| Rotation max [1/min]: | 6000 |
| Rotating direction: | opposite |
| Coolant: | EXT |
| Please note: | Combi bearing |
| Center distance [mm]: | 65 |



| | |
|-----------------------|---|
| 8 030 45 167 | Radial drilling and milling head ER 25 AX UT |
| Weight [kg]: | 5.790 |
| Notation: | 180° reversible |
| Tool drive: | Flat (~DIN 1809) |
| Shank size [mm]: | 45.00 |
| Shank type: | BMT |
| Tool adaption: | ER 25 A - u-tec |
| Gear ratio [i]: | 1:3 |
| Torque max [Nm]: | 12 |
| Rotation max [1/min]: | 18000 |
| Rotating direction: | same |
| Coolant: | EXT |

| Part-# | Name | |
|--|--|------------------|
| | Please note: | stronger bearing |
| | Center distance [mm]: | 77 |
| 8 030 45 169 | Radial drilling and milling head ER 25 AX UT | |
|  | Weight [kg]: | 5.340 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Center distance [mm]: | 65 |
| 8 030 45 198 | Angle-mill- and drill holder ER 25 AX UT IC | |
|  | Weight [kg]: | 5.800 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | opposite |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | Combi bearing |
| | Center distance [mm]: | 65 |
| 8 030 45 211 | Radial drilling and milling head ER 25 AX UT | |
| | Weight [kg]: | 5.770 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 16 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Please note: | stronger bearing |
| | Center distance [mm]: | 77 |
| 8 030 45 239 | Radial drilling and milling head ER 25 AX UT IC | |
| | Weight [kg]: | 5.990 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:3 |
| | Torque max [Nm]: | 12 |

| Part-# | Name |
|--------|------|
|--------|------|

| | |
|-----------------------|------------------|
| Rotation max [1/min]: | 18000 |
| Rotating direction: | same |
| Coolant: | IC/Ext |
| Pressure max [bar]: | 140 |
| Please note: | stronger bearing |
| Center distance [mm]: | 77 |

8 030 45 253 Radial drilling and milling head ER 25 AX UT



| | |
|-----------------------|------------------|
| Weight [kg]: | 5.480 |
| Notation: | 180° reversible |
| Tool drive: | Flat (~DIN 1809) |
| Shank size [mm]: | 45.00 |
| Shank type: | BMT |
| Tool adaption: | ER 25 A - u-tec |
| Gear ratio [i]: | 2:1 |
| Torque max [Nm]: | 63 |
| Rotation max [1/min]: | 3000 |
| Rotating direction: | opposite |
| Coolant: | EXT |
| Please note: | Combi bearing |
| Center distance [mm]: | 65 |

8 030 45 346 Radial drilling and milling head C 3 IC



| | |
|-----------------------|--|
| Notation: | 180° reversible |
| Tool drive: | Flat (~DIN 1809) |
| Shank size [mm]: | 45.00 |
| Shank type: | BMT |
| Tool adaption: | heimatec Capto(TM) C 3 |
| Gear ratio [i]: | 1:1 |
| Torque max [Nm]: | 25 |
| Rotation max [1/min]: | 8000 |
| Rotating direction: | opposite |
| Coolant: | IC/Ext |
| Pressure max [bar]: | 140 |
| Please note: | Check applicability; note tool length! |
| Center distance [mm]: | 65 |

8 030 45 351 Radial drilling and milling head C 3

| | |
|-----------------------|--|
| Notation: | 180° reversible |
| Tool drive: | Flat (~DIN 1809) |
| Shank size [mm]: | 45.00 |
| Shank type: | BMT |
| Tool adaption: | heimatec Capto(TM) C 3 |
| Gear ratio [i]: | 1:1 |
| Torque max [Nm]: | 25 |
| Rotation max [1/min]: | 8000 |
| Rotating direction: | opposite |
| Coolant: | EXT |
| Please note: | Check applicability; note tool length! |
| Center distance [mm]: | 65 |

| Part-# | Name | |
|---------------------|--|------------------------|
| 8 030 45 563 | Radial drilling and milling head Weldon 16 | |
| | Weight [kg]: | 5.850 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | Weldon (DIN 1835 b) 16 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Please note: | Combi bearing |
| | Center distance [mm]: | 65 |
| 8 030 45 599 | Radial drilling and milling head ER 25 AX UT IC | |
| | Weight [kg]: | 5.980 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 16 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | stronger bearing |
| | Center distance [mm]: | 77 |
| 8 030 46 196 | Radial drilling and milling head HT 4 | |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | HT 4 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Please note: | strong version |
| | Center distance [mm]: | 65 |
| 8 030 46 197 | Radial drilling and milling head HT 4 IC | |
| | Weight [kg]: | 5.640 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | HT 4 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | opposite |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |

| Part-# | Name |
|--------|------|
|--------|------|

Center distance [mm]: 65

8 030 46 356



Angle-mill- and drill holder ER 32 AX UT IC

Notation: 180° reversible
 Tool drive: Flat (~DIN 1809)
 Shank size [mm]: 45.00
 Shank type: BMT
 Tool adaption: ER 32 A - u-tec
 Gear ratio [i]: 1:1
 Torque max [Nm]: 50
 Rotation max [1/min]: 6000
 Rotating direction: opposite
 Coolant: IC/Ext
 Pressure max [bar]: 140
 Please note: Combi bearing
 Center distance [mm]: 65

8 030 46 563

Radial drilling and milling head ER 32 AX UT IC

Weight [kg]: 5.480
 Notation: 180° reversible
 Tool drive: Flat (~DIN 1809)
 Shank size [mm]: 45.00
 Shank type: BMT
 Tool adaption: ER 32 A - u-tec
 Gear ratio [i]: 1:1
 Torque max [Nm]: 50
 Rotation max [1/min]: 12000
 Rotating direction: opposite
 Coolant: IC/Ext
 Pressure max [bar]: 140
 Center distance [mm]: 65

8 030 46 564


Radial drilling and milling head ER 32 AX UT

Weight [kg]: 5.120
 Notation: 180° reversible
 Tool drive: Flat (~DIN 1809)
 Shank size [mm]: 45.00
 Shank type: BMT
 Tool adaption: ER 32 A - u-tec
 Gear ratio [i]: 1:1
 Torque max [Nm]: 50
 Rotation max [1/min]: 12000
 Rotating direction: opposite
 Coolant: EXT
 Center distance [mm]: 65

8 030 47 122

Radial drilling and milling head Weldon 25 IC

Weight [kg]: 6.580
 Notation: 180° reversible
 Tool drive: Flat (~DIN 1809)
 Shank size [mm]: 45.00
 Shank type: BMT
 Tool adaption: Weldon (DIN 1835 b) 25
 Gear ratio [i]: 2:1
 Torque max [Nm]: 63
 Rotation max [1/min]: 3000
 Rotating direction: opposite

| Part-# | Name | |
|---|---|-----------------------------|
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | Combi bearing |
| | Center distance [mm]: | 65 |
| 8 031 45 026 | Radial milling head universal arbor 22 | |
|  | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | Universal arbor 22 |
| | Gear ratio [i]: | 2:1 |
| | Torque max [Nm]: | 63 |
| | Rotation max [1/min]: | 3000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Please note: | Combi bearing |
| | Center distance [mm]: | 65 |
| 8 031 45 054 | Radial milling head universal arbor 1" | |
| | Weight [kg]: | 6.040 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | Universal arbor 1" (25,4mm) |
| | Gear ratio [i]: | 2:1 |
| | Torque max [Nm]: | 63 |
| | Rotation max [1/min]: | 3000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Please note: | Combi bearing |
| | Center distance [mm]: | 65 |
| 8 031 46 004 | Radial milling head universal arbor 27 | |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | Universal arbor 27 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Please note: | Combi bearing |
| | Center distance [mm]: | 65 |
| 8 033 45 061 | Radial drilling and milling head ER 25 AX UT | |
| | Weight [kg]: | 5.500 |
| | Notation: | offset; 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 3:1 |
| | Torque max [Nm]: | 32 |

| Part-# | Name | |
|---------------------|---|-------------------------------------|
| | Rotation max [1/min]: | 3000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Please note: | Combi bearing; check applicability! |
| | Center distance [mm]: | 65 |
| 8 037 42 002 | Radial disk mill head arbor 10 | |
| | Weight [kg]: | 4.600 |
| | Notation: | 180° reversible |
| | Version: | ± 30° turnable |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | Arbor 10 |
| | Gear ratio [i]: | 2:1 |
| | Torque max [Nm]: | 32 |
| | Rotation max [1/min]: | 4000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Center distance [mm]: | 78 |
| 8 037 43 004 | Radial disk mill head arbor 13 | |
| | Weight [kg]: | 4.630 |
| | Notation: | 180° reversible |
| | Version: | ± 30° turnable |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | Arbor 13 |
| | Gear ratio [i]: | 2:1 |
| | Torque max [Nm]: | 32 |
| | Rotation max [1/min]: | 4000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Center distance [mm]: | 78 |
| 8 039 45 076 | Radial drilling and milling head ER 25 AX UT | |
| | Weight [kg]: | 5.900 |
| | Notation: | 180° reversible |
| | Version: | double spindle |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same/opposite |
| | Coolant: | EXT |
| | Center distance [mm]: | 65 |



| Part-# | Name |
|--------|------|
|--------|------|

8 039 45 106



Radial drilling and milling head ER 25 AX UT

Weight [kg]: 6.250
 Notation: 180° reversible
 Employment for: Main- and sub spindle
 Version: double spindle
 Tool drive: Flat (~DIN 1809)
 Shank size [mm]: 45.00
 Shank type: BMT
 Tool adaption: ER 25 A - u-tec
 Gear ratio [i]: 1:1
 Torque max [Nm]: 25/Sp.
 Rotation max [1/min]: 12000
 Rotating direction: same
 Coolant: EXT
 Center distance [mm]: 50/86

8 039 46 031



Radial drilling and milling head HT 4

Weight [kg]: 6.400
 Notation: 180° reversible
 Employment for: Main- and sub spindle
 Version: double spindle
 Tool drive: Flat (~DIN 1809)
 Shank size [mm]: 45.00
 Tool adaption: HT 4
 Gear ratio [i]: 1:1
 Torque max [Nm]: 50
 Rotation max [1/min]: 12000
 Rotating direction: same/opposite
 Coolant: EXT
 Center distance [mm]: 65

8 040 44 019

Universal head ± 90° adjustable ER 16

Weight [kg]: 2.460
 Tool drive: Flat (~DIN 1809)
 Shank size [mm]: 45.00
 Shank type: BMT
 Tool adaption: ER 16
 Gear ratio [i]: 1:1
 Torque max [Nm]: 10
 Rotation max [1/min]: 6000
 Rotating direction: same
 Coolant: EXT
 Please note: Note swivel range!
 Center distance [mm]: 55

8 040 44 021

Universal head ± 90° adjustable ER 16

Weight [kg]: 2.700
 Notation: 180° reversible
 Tool drive: Flat (~DIN 1809)
 Shank size [mm]: 45.00
 Shank type: BMT
 Tool adaption: ER 16
 Gear ratio [i]: 1:1
 Torque max [Nm]: 10
 Rotation max [1/min]: 6000
 Rotating direction: same
 Coolant: EXT

| Part-# | Name | |
|---------------------|---|--|
| | Please note: | position can be pinned; note swivel range! |
| | Center distance [mm]: | 55 |
| 8 040 44 023 | Universal head ± 90° adjustable ER 20 | |
| | Weight [kg]: | 2.800 |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 20 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 10 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Please note: | Note swivel range! |
| | Center distance [mm]: | 55 |
| 8 040 44 104 | Universal head ± 90° adjustable ER 16 | |
| | Notation: | 180° reversible |
| | Version: | 45° position can be pinned |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 10 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Center distance [mm]: | 55 |
| 8 043 44 004 | Universal head +105°/-20° adj. ER16AX UTIK | |
| | Weight [kg]: | 5.450 |
| | Notation: | offset |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 25 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | opposite |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 25 |
| | Please note: | 180° reversible |
| | Center distance [mm]: | 50 |
| | Offset [mm]: | 35 |
| 8 043 44 005 | Universal head +105°/-20° adj. ER16 AX UT | |
| | Weight [kg]: | 5.360 |
| | Notation: | offset; 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 25 |



| Part-# | Name |
|--------|------|
|--------|------|

Rotation max [1/min]: 6000
 Rotating direction: opposite
 Coolant: EXT
 Center distance [mm]: 50
 Offset [mm]: 35

8 043 44 006 Universal head +105°/-20° adj. ER16AX UTIK



Weight [kg]: 5.470
 Notation: offset
 Tool drive: Flat (~DIN 1809)
 Shank size [mm]: 45.00
 Shank type: BMT
 Tool adaption: ER 16 A - u-tec
 Gear ratio [i]: 1:2
 Torque max [Nm]: 12
 Rotation max [1/min]: 12000
 Rotating direction: opposite
 Coolant: IC/Ext
 Pressure max [bar]: 25
 Please note: 180° reversible
 Center distance [mm]: 50
 Offset [mm]: 35

8 043 44 007 Universal head +105°/-20° adj. ER16 AX UT

Weight [kg]: 5.410
 Notation: offset
 Tool drive: Flat (~DIN 1809)
 Shank size [mm]: 45.00
 Shank type: BMT
 Tool adaption: ER 16 A - u-tec
 Gear ratio [i]: 1:2
 Torque max [Nm]: 12
 Rotation max [1/min]: 12000
 Rotating direction: opposite
 Coolant: EXT
 Please note: 180° reversible
 Center distance [mm]: 50
 Offset [mm]: 35

8 043 44 042 Universal head +105°/-20° adj. ER16AX UTIK

Weight [kg]: 5.470
 Notation: offset
 Version: at 71,5° position can be pinned
 Tool drive: Flat (~DIN 1809)
 Shank size [mm]: 45.00
 Shank type: BMT
 Tool adaption: ER 16 A - u-tec
 Gear ratio [i]: 1:1
 Torque max [Nm]: 25
 Rotation max [1/min]: 6000
 Rotating direction: opposite
 Coolant: IC/Ext
 Pressure max [bar]: 25
 Please note: 180° reversible
 Center distance [mm]: 50

| Part-# | Name |
|--------|------|
|--------|------|

8 043 45 000



Universal head +105°/-20° adj. ER25 AX UT

Weight [kg]: 5.580
 Notation: offset; 180° reversible
 Tool drive: Flat (~DIN 1809)
 Shank size [mm]: 45.00
 Shank type: BMT
 Tool adaption: ER 25 A - u-tec
 Gear ratio [i]: 1:1
 Torque max [Nm]: 25
 Rotation max [1/min]: 6000
 Rotating direction: opposite
 Coolant: EXT
 Please note: stronger bearing
 Center distance [mm]: 50

8 043 45 004



Universal head +105°/-20° adj. ER25AX UTIK

Weight [kg]: 5.660
 Notation: offset; 180° reversible
 Tool drive: Flat (~DIN 1809)
 Shank size [mm]: 45.00
 Shank type: BMT
 Tool adaption: ER 25 A - u-tec
 Gear ratio [i]: 1:1
 Torque max [Nm]: 25
 Rotation max [1/min]: 6000
 Rotating direction: opposite
 Coolant: IC/Ext
 Pressure max [bar]: 25
 Please note: stronger bearing
 Center distance [mm]: 50
 Offset [mm]: 35

8 043 45 005

Universal head +105°/-20° adj. ER25AX UTIK

Weight [kg]: 5.610
 Notation: offset; 180° reversible
 Version: at 42,9° position can be pinned
 Tool drive: Flat (~DIN 1809)
 Shank size [mm]: 45.00
 Shank type: BMT
 Tool adaption: ER 25 A - u-tec
 Gear ratio [i]: 1:1
 Torque max [Nm]: 25
 Rotation max [1/min]: 6000
 Rotating direction: opposite
 Coolant: IC/Ext
 Pressure max [bar]: 25
 Please note: stronger bearing
 Center distance [mm]: 50
 Offset [mm]: 35


8 043 45 015

Universal head +105°/-20° adj. Weldon 16



Notation: offset; 180° reversible
 Tool drive: Flat (~DIN 1809)
 Shank size [mm]: 45.00
 Shank type: BMT
 Tool adaption: Weldon (DIN 1835 b) 16 special
 Gear ratio [i]: 1:1




| Part-# | Name | |
|---------------------|--|--|
| | Torque max [Nm]: | 25 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Please note: | stronger bearing |
| | Center distance [mm]: | 50 |
| | Offset [mm]: | 35 |
| 8 043 45 017 | Universal head +105°/-20° adj. ER25 AX UT | |
| | Weight [kg]: | 5.590 |
| | Notation: | offset; 180° reversible; at 45° position can be pinned |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 25 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Please note: | stronger bearing |
| | Center distance [mm]: | 50 |
| 8 043 46 002 | Universal head +105°/-20° adj. Weldon 20 | |
| | Weight [kg]: | 5.790 |
| | Notation: | offset; 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | Weldon (DIN 1835 b) 20 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 25 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Please note: | stronger bearing |
| | Center distance [mm]: | 50 |
| | Offset [mm]: | 35 |
| 8 050 43 009 | Multispindle drilling head ER 11 | |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 11 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 10/Sp. |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| 8 050 44 005 | Multispindle drilling head ER 16 AX UT | |
| | Weight [kg]: | 3.700 |
| | Version: | 2-spindles |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:1 |




| Part-# | Name | |
|---|---|-------------------------|
| | Torque max [Nm]: | 25/Sp. |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| 8 050 44 045 | Multispindle drilling head ER 16 AX UT | |
| | Weight [kg]: | 5.840 |
| | Notation: | offset, 180° reversible |
| | Version: | 2-spindles |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 8/Sp. |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Offset [mm]: | 64,359 |
| 8 053 44 032 | Multispindle radial head ER 16 AX UT | |
| | Weight [kg]: | 6.120 |
| | Notation: | 180° reversible |
| | Version: | 2-spindles |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 8 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Center distance [mm]: | 65 |
| 8 053 44 062 | Multispindle radial head ER16 AX UT IC | |
|  | Weight [kg]: | 6.580 |
| | Notation: | 180° reversible |
| | Version: | 2-spindles |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 32/Sp |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Center distance [mm]: | 65 |



| Part-# | Name | |
|---|---|--|
| 8 053 44 063 | Multispindle radial head ER16 AX UT IC | |
|  | Notation: | 180° reversible |
| | Version: | 2-spindles |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 16/Sp |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Center distance [mm]: | 65 |
| 8 053 44 065 | Multispindle radial head ER 16 AX UT | |
|  | Weight [kg]: | 6.400 |
| | Notation: | 180° reversible |
| | Version: | 2-spindles |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 16/Sp |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Center distance [mm]: | 65 |
| 8 053 44 066 | Multispindle radial head ER 16 AX UT | |
|  | Notation: | 180° reversible |
| | Version: | 2-spindles |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 32/Sp |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Center distance [mm]: | 65 |
| 8 053 44 067 | Multispindle radial head ER 20 AX UT | |
| | Notation: | 180° reversible |
| | Version: | 2-spindles |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 20 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 32/Sp |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Please note: | Check applicability; note tool length! |

| Part-# | Name | |
|--|---|--|
| | Center distance [mm]: | 75 |
| 8 053 44 074 | Multispindle radial head ER 20 AX UTIK | |
|  | Notation: | 180° reversible |
| | Version: | 2-spindles |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 45.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 20 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 32/Sp |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | Check applicability; note tool length! |
| | Center distance [mm]: | 75 |
| 8 200 02 001 | Cover plate | |
| | Weight [kg]: | 0.320 |
| | Shank type: | - |
| 8 202 00 010 | Basic holder longitudinal seat FN 12 | |
|  | Weight [kg]: | 0.920 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | Interface FN 12 |
| | Coolant: | EXT |
| 8 224 01 020 | Cut-off holder sq. 20 | |
| | Weight [kg]: | 2.020 |
| | Employment for: | right cutting tools |
| | Version: | Special; edge on side of turret |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | Sq. 20 |
| | Coolant: | EXT |
| 8 224 03 016 | Universal turning holder sq. 3/4" IC | |
|  | Weight [kg]: | 2.630 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | Sq. 3/4" (19,05mm) |
| | | Sq. 3/4" (19,05mm) |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 100 |
| | Please note: | Key rail |


| Part-# | Name | |
|--|---|--|
| 8 224 04 000 | Universal turning holder sq. 20 | |
|  | Weight [kg]: | 2.640 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | Sq. 20 |
| | | Sq. 20 |
| | Coolant: | EXT |
| 8 224 04 035 | Universal turning holder sq. 20 IC | |
|  | Weight [kg]: | 2.620 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | Sq. 20 |
| | Coolant: | IC |
| 8 224 04 068 | Universal turning holder sq. 20 IC | |
|  | Weight [kg]: | 2.610 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | Sq. 20 |
| | | Sq. 20 |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 100 |
| | Please note: | Key rail |
| 8 229 05 004 | Tool holder C 3 IC | |
| | Weight [kg]: | 2.980 |
| | Notation: | 180° reversible |
| | Version: | right |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | heimatec Capto(TM) C 3 |
| | Coolant: | IC |
| | Please note: | Check applicability; note tool length! |
| | Offset [mm]: | 65 |
| 8 229 05 005 | Tool holder C 3 IC | |
| | Weight [kg]: | 1.590 |
| | Notation: | 180° reversible |
| | Version: | right |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | heimatec Capto(TM) C 3 |
| | Coolant: | IC |
| | Please note: | Check applicability; note tool length! |
| | Offset [mm]: | 27 |

| Part-# | Name | |
|---------------------|------------------------------------|--|
| 8 240 05 034 | Boring bar holder Ø 16 | |
| | Weight [kg]: | 4.360 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | Ø 16 |
| | Coolant: | IC/Ext |
| | Center distance [mm]: | 75 |
| 8 240 05 059 | Tool holder C 3 IC | |
| | Weight [kg]: | 4.130 |
| | Notation: | 180° reversible |
| | Version: | right |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | heimatec Capto(TM) C 3 |
| | Coolant: | IC |
| | Please note: | Check applicability; note tool length! |
| | Center distance [mm]: | 80 |
| 8 240 05 060 | Tool holder C 3 IC | |
| | Weight [kg]: | 3.190 |
| | Notation: | 180° reversible |
| | Version: | offset; right |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | heimatec Capto(TM) C 3 |
| | Coolant: | IC |
| | Please note: | Check applicability; note tool length! |
| | Center distance [mm]: | 80 |
| 8 240 06 034 | Boring bar holder Ø 20 | |
| | Weight [kg]: | 4.280 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | Ø 20 |
| | Coolant: | IC/Ext |
| | Center distance [mm]: | 75 |
| 8 240 07 038 | Boring bar holder Ø 25 | |
| | Weight [kg]: | 4.160 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | Ø 25 |
| | Coolant: | IC/Ext |
| | Center distance [mm]: | 75 |
| 8 240 07 050 | Boring bar holder Ø 1 1/4 " | |
| | Weight [kg]: | 3.790 |
| | Notation: | offset |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | Ø 1 1/4" (31,75mm) |
| | Coolant: | IC/Ext |
| | Center distance [mm]: | 75 |


| Part-# | Name | |
|--------------|--|---------------------------------------|
| 8 240 08 000 | Boring bar holder Ø 32  | Weight [kg]: 3.740 |
| | | Notation: offset |
| | | Shank type: BMT |
| | | Machine adaption: Centering bolt ø 12 |
| | | Tool adaption: Ø 32 |
| | | Coolant: IC/Ext |
| | | Center distance [mm]: 75 |
| 8 240 08 046 | Boring bar holder Ø 32 | Weight [kg]: 3.940 |
| | | Notation: 180° reversible |
| | | Shank type: BMT |
| | | Machine adaption: Centering bolt ø 12 |
| | | Tool adaption: Ø 32 |
| | | Coolant: IC/Ext |
| | | Center distance [mm]: 75 |
| 8 240 08 074 | Boring bar holder Ø 1 1/2" | Weight [kg]: 4.000 |
| | | Shank type: BMT |
| | | Machine adaption: Centering bolt ø 12 |
| | | Tool adaption: Ø 1 1/2" (38,1mm) |
| | | Coolant: IC/Ext |
| | | Center distance [mm]: 75 |
| 8 240 09 002 | Boring bar holder Ø 40  | Weight [kg]: 2.660 |
| | | Version: offset |
| | | Shank type: BMT |
| | | Machine adaption: Centering bolt Ø 12 |
| | | Tool adaption: Ø 40 |
| | | Coolant: IC/Ext |
| | | Center distance [mm]: 75 |
| 8 240 09 013 | Boring bar holder Ø 40 | Weight [kg]: 3.950 |
| | | Shank type: BMT |
| | | Machine adaption: Centering bolt Ø 12 |
| | | Tool adaption: Ø 40 |
| | | Coolant: IC/Ext |
| | | Center distance [mm]: 75 |
| 8 244 04 019 | Combi facing holder sq. 20 | Weight [kg]: 3.700 |
| | | Shank type: BMT |
| | | Machine adaption: Centering bolt ø 12 |
| | | Tool adaption: Sq. 20 |
| | | Coolant: EXT |
| 8 249 05 008 | Double tool holder C 3 IC | Weight [kg]: 4.860 |
| | | Employment for: Main- and sub spindle |
| | | Version: right |
| | | Shank type: BMT |
| | | Machine adaption: Centering bolt ø 12 |
| | | Tool adaption: heimatec Capto(TM) C 3 |


| Part-# | Name | |
|---|---|--|
| | | heimatec Capto(TM) C 3 IC Check applicability; note tool length! 80 |
| 8 250 05 002 | Multiple tool holder C 3 IC | |
| | Coolant: | |
| | Please note: | |
| | Center distance [mm]: | |
| | Weight [kg]: | 2.140 |
| | Employment for: | Main- and sub spindle |
| | Version: | right |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | heimatec Capto(TM) C 3 heimatec Capto(TM) C 3 |
| | Coolant: | IC |
| | Please note: | Check applicability; note tool length! |
| | Offset [mm]: | 27 27 |
| 8 250 05 003 | Multiple tool holder C 3 IC | |
| | Weight [kg]: | 3.730 |
| | Employment for: | Main- and sub spindle |
| | Version: | right |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | heimatec Capto(TM) C 3 heimatec Capto(TM) C 3 |
| | Coolant: | IC |
| | Please note: | Check applicability; note tool length! |
| | Offset [mm]: | 65 65 |
| 8 251 03 002 | Combi double turning holder sq. 3/4"IC | |
|  | Weight [kg]: | 4.360 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | Sq. 3/4" (19,05mm) Sq. 3/4" (19,05mm) Sq. 3/4" (19,05mm) Sq. 3/4" (19,05mm) |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 100 |
| | Please note: | Key rail |
| 8 251 04 002 | Combi double turning holder sq. 20 | |
|  | Weight [kg]: | 4.380 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | Sq. 20 Sq. 20 Sq. 20 Sq. 20 |
| | Coolant: | EXT |

| Part-# | Name | |
|---|--|-------------------------|
| 8 251 04 003 | Combi double turning holder sq. 3/4" | |
|  | Weight [kg]: | 4.410 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | Sq. 3/4" (19,05mm) |
| | | Sq. 3/4" (19,05mm) |
| | | Sq. 3/4" (19,05mm) |
| | | Sq. 3/4" (19,05mm) |
| | Coolant: | EXT |
| 8 251 04 059 | Combi double turning holder sq. 20 IC | |
|  | Weight [kg]: | 4.360 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | Sq. 20 |
| | | Sq. 20 |
| | | Sq. 20 |
| | | Sq. 20 |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 100 |
| | Please note: | Key rail |
| 8 253 07 000 | Double boring bar holder Ø 25 | |
|  | Weight [kg]: | 2.320 |
| | Notation: | offset, 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | Ø 25 |
| | | Ø 25 |
| | Coolant: | IC/Ext |
| | Center distance [mm]: | 50/85 |
| 8 253 07 003 | Multiple boring bar holder Ø 1" | |
|  | Weight [kg]: | 2.530 |
| | Notation: | offset, 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | Ø 1" (25,4mm) |
| | | Ø 1" (25,4mm) |
| | Coolant: | IC/Ext |
| | Center distance [mm]: | 50/85 |
| 8 253 07 004 | Double boring bar holder Ø 1" | |
|  | Weight [kg]: | 3.740 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | Ø 1" (25,4mm) |
| | | Ø 1" (25,4mm) |
| | Coolant: | IC/Ext |
| | Center distance [mm]: | 50/85 |

| Part-# | Name | | | |
|---|--------------------------------------|---------------------------------------|--|---------------------------------------|
| 8 253 07 006 | Double boring bar holder Ø 25 | Weight [kg]: 3.710 | | |
| | | Notation: 180° reversible | | |
|  | | Shank type: BMT | | |
| | | Machine adaption: Centering bolt Ø 12 | | |
| | | Tool adaption: Ø 25 | | |
| | | Ø 25 | | |
| | | Coolant: IC/Ext | | |
| | | Center distance [mm]: 50/85 | | |
| | | 8 259 01 006 | Multiple turning holder 4x sq. 20 | 4.700 |
| | | | | Weight [kg]: 4.700 |
| | | | | Employment for: Main- and sub spindle |
| | | | | Version: Y-axes offset |
| Shank type: BMT | | | | |
| Machine adaption: Centering bolt ø 12 | | | | |
| Tool adaption: Sq. 20 | | | | |
| Sq. 20 | | | | |
| Sq. 20 | | | | |
| Sq. 20 | | | | |
| Coolant: EXT | | | | |
| 8 259 05 001 | Multiple tool holder C 3 IC | 5.590 | | |
| | | Weight [kg]: 5.590 | | |
| | | Employment for: Main- and sub spindle | | |
| | | Version: right; Y-axes offset | | |
| | | Shank type: BMT | | |
| | | Machine adaption: Centering bolt ø 12 | | |
| | | Tool adaption: heimatec Capto(TM) C 3 | | |
| | | heimatec Capto(TM) C 3 | | |
| | | heimatec Capto(TM) C 3 | | |
| | | heimatec Capto(TM) C 3 | | |
| | | Coolant: IC | | |
| Please note: Check applicability; note tool length! not | | | | |
| Offset [mm]: 65 | | | | |
| 65 | | | | |
| 8 259 05 002 | Multiple tool holder C 3 IC | 6.330 | | |
| | | Weight [kg]: 6.330 | | |
| | | Employment for: Main- and sub spindle | | |
| | | Version: right; Y-axes offset | | |
| | | Shank type: BMT | | |
| | | Machine adaption: Centering bolt ø 12 | | |
| | | Tool adaption: heimatec Capto(TM) C 3 | | |
| | | heimatec Capto(TM) C 3 | | |
| | | heimatec Capto(TM) C 3 | | |
| | | heimatec Capto(TM) C 3 | | |
| | | Coolant: IC | | |
| Please note: Check applicability; note tool length! | | | | |
| Center distance [mm]: 80 | | | | |

| Part-# | Name | |
|---------------------|------------------------------------|--|
| 8 259 05 003 | Multiple tool holder C 3 IC | |
| | Notation: | 180° reversible |
| | Version: | right; Y-axes offset |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | heimatec Capto(TM) C 3 heimatec Capto(TM) C 3 |
| | Coolant: | IC |
| | Please note: | Check applicability; note tool length! |
| | Center distance [mm]: | 80 |
| | Offset [mm]: | +32 -32 |
| 8 259 05 004 | Multiple tool holder C 3 IC | |
| | Weight [kg]: | 4.390 |
| | Notation: | 180° reversible |
| | Version: | right; offset; Y-axes offset |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | heimatec Capto(TM) C 3 heimatec Capto(TM) C 3 |
| | Coolant: | IC |
| | Please note: | Check applicability; note tool length! |
| | Center distance [mm]: | 80 |
| 8 259 05 005 | Multiple tool holder C 3 IC | |
| | Weight [kg]: | 4.210 |
| | Employment for: | Main- and sub spindle |
| | Version: | right; Y-axes offset |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | heimatec Capto(TM) C 3 heimatec Capto(TM) C 3 heimatec Capto(TM) C 3 heimatec Capto(TM) C 3 |
| | Coolant: | IC |
| | Please note: | Check applicability; note tool length!; not |
| | Offset [mm]: | 27 27 |
| 8 259 05 006 | Multiple tool holder C 3 IC | |
| | Weight [kg]: | 2.840 |
| | Notation: | 180° reversible |
| | Version: | right; Y-axes offset |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | heimatec Capto(TM) C 3 heimatec Capto(TM) C 3 |
| | Coolant: | IC |
| | Please note: | Check applicability; note tool length! |
| | Offset [mm]: | 27 |

| Part-# | Name | |
|--------------|--|--|
| 8 259 05 007 | Multiple tool holder C 3 IC |  |
| | | <p>Weight [kg]: 4.000 Notation: 180° reversible Version: right; Y-axes offset Shank type: BMT Machine adaption: Centering bolt ø 12 Tool adaption: heimatec Capto(TM) C 3 heimatec Capto(TM) C 3 Coolant: IC Pressure max [bar]: 100 Please note: Check applicability; note tool length! Offset [mm]: 65</p> |
| 8 259 09 001 | Multiple holder ø25 and sq. 20 | <p>Weight [kg]: 3.980 Notation: 180° reversible Shank type: BMT Machine adaption: Centering bolt ø 12 Tool adaption: ø25/ sq. 20 ø25/ sq. 20 Coolant: IC/Ext Center distance [mm]: 50/85</p> |
| | | |
| 8 261 08 000 | Tool holder for centering insert | <p>Weight [kg]: 5.270 Notation: 180° reversible Shank type: BMT Machine adaption: Centering bolt ø 12 Tool adaption: ø 32 Coolant: EXT Please note: Price without centering point Center distance [mm]: 55</p> |
| | | |
| 8 263 09 000 | Tool holder with rotating centering point | <p>Weight [kg]: 4.070 Notation: 180° reversible Shank type: BMT Machine adaption: Centering bolt ø 12 Rotation max [1/min]: 6000 Coolant: EXT Please note: Taper roller bearings Center distance [mm]: 75</p> |
| | | |
| 8 263 09 007 | Tool holder with rotating centering point | <p>Weight [kg]: 6.410 Notation: 180° reversible; offset Shank type: BMT Machine adaption: Centering bolt ø 12 Rotation max [1/min]: 6000 Coolant: EXT Center distance [mm]: 85</p> |
| | | |

| Part-# | Name | |
|---------------------|---|--|
| 8 320 02 017 | Cut-off holder, height adjustable SH 26 IC | |
| | Weight [kg]: | 1.410 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | Clampshaft SH 26 |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 70 |
| 8 320 02 018 | Cut-off holder, height adjustable SH 26 IC | |
| | Weight [kg]: | 1.560 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: | Clampshaft SH 26 |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 70 |
| | Please note: | Clampshaft internal |
| 8 320 09 003 | Cut-off holder, height adjustable 845 IC | |
| | Weight [kg]: | 1.390 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering bolt ø 12 |
| | Tool adaption: |  System 845 |
| | Coolant: | IC |
| | Pressure max [bar]: | 70 |

heimatec.u-tec®

heimatec.com

Products / Tool change systems /
u-tec® Tool-changing system



versions see catalog



heimatec.easy-quick

heimatec.com

Products / Tool change systems /
easy-quick HT quick-changing system



versions see catalog



heimatec.Capto™

heimatec.com

Products / Tool change systems /
heimatec.Capto™ quick-changing system



versions see catalog



heimatec.accessories

heimatec.com

Products / Accessories



versions see catalog





● heimatec overseas branches

○ global representations of heimatec

heimatec[®]

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
77871 Renchen
Germany

T +49 7843 9466 0
www.heimatec.com
info@heimatec.com

Please find the contact details of our worldwide trading partners on our website:
<https://heimatec.com/business-partners>