

TOPSELLER -
many more available!

Live Tools


heimatec®

Tsugami


M06-M08 D/SD/SY - BMT 65

Part-#	Tool adaption	Rotation max [1/min]	Gear ratio	Coolant	Pressure max.	Center distance
Axial drilling and milling head						
8 010 66 260	ER 32 A - u-tec	12.000	1:1	EXT	--	--
8 010 66 261	ER 32 A - u-tec	12.000	1:1	IC/Ext	100 bar	--
Axial drilling and milling head, offset						
8 019 66 051	ER 32 A - u-tec	6.000	1:1	EXT	--	--
8 019 66 052	ER 32 A - u-tec	6.000	1:1	IC/Ext	140 bar	--
Radial drilling and milling head						
8 030 66 241	ER 32 A - u-tec	12.000	1:1	IC/Ext	140 bar	85 mm
8 030 66 254	ER 32 A - u-tec	12.000	1:1	EXT	--	85 mm
Universal head						
8 040 64 023	ER 20 A - u-tec	10.000	1:1	EXT	--	60 mm
8 040 64 024	ER 20 A - u-tec	10.000	1:1	IC/Ext	140 bar	60 mm
Universal head, offset						
8 043 65 018	ER 25 A - u-tec	6.000	1:1	EXT	--	60 mm

Illustrations similar.



8 010 66 260



8 010 66 261



8 030 66 241



8 030 66 254



8 040 64 023

TOPSELLER -
many more available!

Static Tools

heimatec®

Tsugami


M06-M08 D/SD/SY - BMT 65

Part-#	Tool adaption	Coolant	Pressure max.	Center distance
Universal turning holder				
8 224 15 032	Sq. 25	EXT	--	--
Boring bar holder				
8 240 17 073	Ø 25	IC/Ext	--	90 mm
8 240 18 066	Ø 32	IC/Ext	--	90 mm
8 240 19 085	Ø 40	IC/Ext	--	90 mm
Combi facing holder				
8 244 15 014	Sq. 25	EXT	--	--
Double turning holder				
8 251 15 024	Sq. 25	EXT	--	--
Double boring bar holder				
8 253 19 004	Ø 40	IC/Ext	100 bar	--
Cut-off holder, height adjustable				
8 320 13 030	Clampshaft SH 32	IC/Ext	70 bar	--


Illustrations similar.



8 240 17 073



8 240 18 066



8 253 19 004