

**TOPSELLER -**  
many more available!

Live Tools


**heimatec**®

# Miyano

## BNJ 42 SY2/SY3/SY5

Part-#	Tool adaption	Rotation max [1/min]	Gear ratio	Coolant	Pressure max.	Center distance
<b>Axial drilling and milling head</b>						
8 010 45 224	<b>ER 25 A - u-tec</b>	15.000	1:1	EXT	--	--
8 010 45 225	<b>ER 25 A - u-tec</b>	12.000	1:1	IC/Ext	100 bar	--
<b>Radial drilling and milling head</b>						
8 030 45 136	<b>ER 25 A - u-tec</b>	12.000	1:1	IC/Ext	140 bar	<b>65 mm</b>
8 030 45 169	<b>ER 25 A - u-tec</b>	12.000	1:1	EXT	--	<b>65 mm</b>
<b>Radial drilling and milling head, double spindle</b>						
8 039 45 076	<b>ER 25 A - u-tec</b>	12.000	1:1	EXT	--	<b>65 mm</b>
<b>Universal head, offset</b>						
8 043 44 005	<b>ER 16 A - u-tec</b>	6.000	1:1	EXT	--	<b>50 mm</b>
8 043 45 000	<b>ER 25 A - u-tec</b>	6.000	1:1	EXT	--	<b>50 mm</b>
<b>Multispindle drilling head</b>						
8 050 44 005	<b>ER 16 A - u-tec</b>	12.000	1:1	EXT	--	--


Illustrations similar.




8 010 45 224



8 030 45 136



8 039 45 076



8 043 44 005



8 050 44 005

**TOPSELLER -**  
many more available!

Static Tools

**heimatec**®

# Miyano

## BNJ 42 SY2/SY3/SY5

Part-#	Tool adaption	Coolant	Pressure max.	Center distance
<b>Universal turning holder</b>				
8 224 04 000	<b>Sq. 20</b>	EXT	--	--
8 224 04 068	<b>Sq. 20</b>	IC/Ext	100 bar	--
<b>Boring bar holder</b>				
8 240 08 000	<b>Ø 32</b>	IC/Ext	--	<b>75 mm</b>
8 240 09 002	<b>Ø 40</b>	IC/Ext	--	<b>75 mm</b>
<b>Double boring bar holder</b>				
8 253 07 000	<b>Ø 25</b>	IC/Ext	--	--

*Illustrations similar.*



8 224 04 000



8 224 04 068



8 240 08 000



8 253 07 000