

Gildemeister  
**CTX 510 ECO**  
**line DIN 5482**



# High-tech from heimatec - heimatec - Tools and systems for productive turning and milling

heimatec belongs to the international technology and quality leaders for precision tools and specializes in the development and production of high-precision static and live tools for all CNC lathes, CNC turn-/mill machines and CNC machining centers.

The range of products\* spans from static BMT and VDI tool holders, live tools up to highly complex customer-specific individual solutions. heimatec, headquartered in Renchen, has a own subsidiary in Asia and India and numerous representatives as well as trading partners all over the world.

## \*OUR PRODCUTS

Static tool holders

Live tool units

Precision tools

Tools for turning and machining centres

Tools for swiss type lathes

Tool changing and uick-change systems

Tool systems for gear production

Digital tool management

This catalogue, including all its parts, is protected by copyright. Any use outside the restricted limitations of the Copyright Act without the consent of heimatec is inadmissible and liable to prosecution. This applies in particular to duplication, translation, microfilming and storage and processing in electronic systems.

**heimatec GmbH** reserves the right to make technical changes at any time without giving prior notice. This applies in particular to adjustments at any time to meet new or changed international standards, or in case of further developments of our products or manufacturing processes.

The current version of our General Terms and Conditions can be found on our website.

Part-#	Name	
<b>8 010 46 001</b>	<b>Axial drilling and milling head ER 32</b>	
	Weight [kg]:	3.270
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
Coolant:	EXT	
<b>8 010 46 004</b>	<b>Axial drilling and milling head C 20</b>	
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	DIN 6388 - C 20
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
<b>8 010 46 195</b>	<b>Axial drilling and milling head ER 32 AX UT IC</b>	
	Weight [kg]:	3.340
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
Coolant:	IC/Ext	
Pressure max [bar]:	25	
Please note:	round housing Ø 84	
<b>8 010 46 196</b>	<b>Axial drilling and milling head ER 32 AX UT</b>	
	Weight [kg]:	3.200
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
Coolant:	EXT	
Please note:	round housing ø 84	
<b>8 010 46 281</b>	<b>Axial drilling and milling head ER 32 IC</b>	
	Weight [kg]:	3.400
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32
Gear ratio [i]:	1:1	
Torque max [Nm]:	50	

Part-#	Name	
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	25
	Please note:	round housing ø 84
<b>8 010 47 003</b>	<b>Axial drilling and milling head Weldon 1" IC</b>	
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Weldon (DIN 1835 b) 1" (25,4mm)
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	5000
	Rotating direction:	same
	Coolant:	IC/Ext
<b>8 010 47 032</b>	<b>Axial drilling and milling head Weldon 25 IC</b>	
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Weldon (DIN 1835 b) 25
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	25
	Please note:	round housing ø 84
<b>8 010 47 035</b>	<b>Axial drilling and milling head Weldon 25</b>	
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Weldon (DIN 1835 b) 25
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	round housing ø 84
<b>8 010 47 103</b>	<b>Axial drilling and milling head HT 5 IC</b>	
	Weight [kg]:	3.440
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	HT 5
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	25
	Please note:	round housing ø 84

Part-#	Name	
<b>8 010 47 104</b>	<b>Axial drilling and milling head HT 5</b>	
	Weight [kg]:	3.210
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	HT 5
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	round housing ø 84
<b>8 010 47 105</b>	<b>Axial drilling and milling head ER 40 IC</b>	
	Weight [kg]:	3.620
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 40
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	25
	Please note:	stronger bearing; round housing Ø 84
<b>8 011 44 000</b>	<b>Axial milling head universal arbor 16</b>	
	Weight [kg]:	3.320
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Universal arbor 16
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
<b>8 011 45 002</b>	<b>Axial milling head universal arbor 22</b>	
	Weight [kg]:	3.440
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Universal arbor 22
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
<b>8 011 48 000</b>	<b>Axial milling head universal arbor 40</b>	
	Version:	Special
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Universal arbor 40
	Gear ratio [i]:	1:1

Part-#	Name	
	Torque max [Nm]:	50
	Rotation max [1/min]:	5000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	stronger bearing
<b>8 013 46 001</b>	<b>Axial drilling and milling head ER 32</b>	
	Weight [kg]:	7.220
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32
	Gear ratio [i]:	3:1
	Torque max [Nm]:	75
	Rotation max [1/min]:	3000
	Rotating direction:	same
	Coolant:	EXT
<b>8 013 47 001</b>	<b>Axial drilling and milling head HT 5</b>	
	Weight [kg]:	7.200
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	HT 5
	Gear ratio [i]:	3:1
	Torque max [Nm]:	75
	Rotation max [1/min]:	3000
	Rotating direction:	same
	Coolant:	EXT
<b>8 014 46 000</b>	<b>Axial milling head universal arbor 27</b>	
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Universal arbor 27
	Gear ratio [i]:	4:1
	Torque max [Nm]:	100
	Rotation max [1/min]:	1500
	Rotating direction:	same
	Coolant:	EXT
	Please note:	stronger bearing
<b>8 019 47 035</b>	<b>Axial drilling and milling head HT 5 IC</b>	
	Notation:	offset
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	HT 5
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	25
	Please note:	stronger bearing
	Offset [mm]:	50

Part-#	Name	
<b>8 030 45 033</b>	<b>Radial drilling and milling head C 16</b>	
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	DIN 6388 - C 16
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	4000
	Rotating direction:	opposite
	Coolant:	EXT
<b>8 030 45 039</b>	<b>Radial drilling and milling head ER 25</b>	
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 25
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Coolant:	EXT
	Please note:	Special version
<b>8 030 45 086</b>	<b>Radial drilling and milling head ER 25</b>	
	Weight [kg]:	5.100
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 25
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	stronger version
	Center distance [mm]:	69
<b>8 030 46 027</b>	<b>Radial drilling and milling head ER 32</b>	
	Weight [kg]:	5.120
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Center distance [mm]:	69
<b>8 030 46 081</b>	<b>Radial drilling and milling head ER 32 IC</b>	
	Weight [kg]:	5.680
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000

Part-#	Name	
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Center distance [mm]:	69
<b>8 030 46 102</b>	<b>Radial drilling and milling head Weldon 20 IC</b>	
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Weldon (DIN 1835 b) 20
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	25
	Please note:	stronger bearing
<b>8 030 46 158</b>	<b>Radial drilling and milling head ER 32</b>	
	Weight [kg]:	5.380
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
	Center distance [mm]:	69
<b>8 030 46 332</b>	<b>Radial drilling and milling head ER 32 AX UT</b>	
	Weight [kg]:	5.050
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Center distance [mm]:	69
<b>8 030 46 340</b>	<b>Radial drilling and milling head ER 32 AX UT IC</b>	
	Weight [kg]:	5.500
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	IC/Ext

Part-#	Name	
	Pressure max [bar]:	140
	Center distance [mm]:	69
<b>8 030 46 512</b>	<b>Radial drilling and milling head ER 32 AX UT</b>	
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	2:1
	Torque max [Nm]:	63
	Rotation max [1/min]:	3000
	Rotating direction:	opposite
	Coolant:	EXT
	Center distance [mm]:	69
<b>8 030 47 009</b>	<b>Radial drilling and milling head C 25</b>	
	Weight [kg]:	5.380
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	DIN 6388 - C 25
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Center distance [mm]:	69
<b>8 030 47 027</b>	<b>Radial drilling and milling head ER 40 IC</b>	
	Weight [kg]:	5.840
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 40
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Center distance [mm]:	69
<b>8 030 47 038</b>	<b>Radial drilling and milling head HT 5</b>	
	Weight [kg]:	5.100
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	HT 5
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Center distance [mm]:	69

Part-#	Name	
<b>8 030 47 090</b>	<b>Radial drilling and milling head ER 40</b>	
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 40
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
	Center distance [mm]:	69
<b>8 031 44 000</b>	<b>Radial milling head universal arbor 16</b>	
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Universal arbor 16
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	4000
	Rotating direction:	opposite
	Coolant:	EXT
	Center distance [mm]:	54
<b>8 031 44 007</b>	<b>Radial milling head universal arbor 16</b>	
	Weight [kg]:	5.100
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Universal arbor 16
	Gear ratio [i]:	2:1
	Torque max [Nm]:	63
	Rotation max [1/min]:	3000
	Rotating direction:	opposite
	Coolant:	EXT
	Center distance [mm]:	69
<b>8 031 45 000</b>	<b>Radial milling head universal arbor 22</b>	
	Weight [kg]:	3.700
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Universal arbor 22
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	no
	Center distance [mm]:	54

Part-#	Name	
<b>8 031 46 001</b>	<b>Radial milling head universal arbor 27</b>	
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Universal arbor 27
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	4000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	stronger bearing
	Center distance [mm]:	69
<b>8 031 47 000</b>	<b>Radial milling head universal arbor 32</b>	
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Universal arbor 32
	Gear ratio [i]:	1,625:1
	Torque max [Nm]:	80
	Rotation max [1/min]:	4000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	stronger bearing
	Center distance [mm]:	69
<b>8 033 44 009</b>	<b>Radial drilling and milling head ER 16</b>	
	Weight [kg]:	5.860
	Notation:	offset
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 16
	Gear ratio [i]:	1:2
	Torque max [Nm]:	12
	Rotation max [1/min]:	8000
	Rotating direction:	same
	Coolant:	EXT
<b>8 033 45 000</b>	<b>Radial drilling and milling head ER 25</b>	
	Weight [kg]:	5.920
	Notation:	offset
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 25
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
	Center distance [mm]:	85

Part-#	Name	
<b>8 033 45 001</b>	<b>Radial drilling and milling head C 16</b>	
	Notation:	offset
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	DIN 6388 - C 16
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
<b>8 033 45 007</b>	<b>Radial drilling and milling head Weldon 16</b>	
	Notation:	offset
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Weldon (DIN 1835 b) 16
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	stronger bearing
	Center distance [mm]:	100
<b>8 033 46 004</b>	<b>Radial drilling and milling head C 4</b>	
	Notation:	offset
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	heimatec Capto(TM) C 4
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	4000
	Rotating direction:	same
	Coolant:	EXT
	Center distance [mm]:	94
	Offset [mm]:	66,5
<b>8 033 46 009</b>	<b>Radial drilling and milling head ER 32</b>	
	Weight [kg]:	7.520
	Notation:	offset
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32
	Gear ratio [i]:	1,625:1
	Torque max [Nm]:	63
	Rotation max [1/min]:	4000
	Rotating direction:	same
	Coolant:	EXT
	Center distance [mm]:	100

Part-#	Name	
<b>8 033 46 027</b>	<b>Radial drilling and milling head ER 32 IC</b>	
	Notation:	offset
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Center distance [mm]:	100
<b>8 033 46 029</b>	<b>Radial drilling and milling head C 4 IC</b>	
	Weight [kg]:	10.180
	Notation:	offset
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	heimatec Capto(TM) C 4
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	4000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	25
<b>8 033 46 037</b>	<b>Radial drilling and milling head ER 32</b>	
	Weight [kg]:	8.680
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32
	Gear ratio [i]:	1:2
	Torque max [Nm]:	25
	Rotation max [1/min]:	12000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	stronger bearing
<b>8 033 46 038</b>	<b>Radial drilling and milling head Weldon 20 IC</b>	
	Notation:	offset
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Weldon (DIN 1835 b) 20
	Gear ratio [i]:	1,625:1
	Torque max [Nm]:	63
	Rotation max [1/min]:	3000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	25
	Please note:	stronger bearing
	Center distance [mm]:	100

Part-#	Name	
<b>8 033 46 112</b>	<b>Radial drilling and milling head ER 32 AX UT</b>	
	Weight [kg]:	7.480
	Notation:	offset
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
	Center distance [mm]:	100
<b>8 033 46 135</b>	<b>Radial drilling and milling head ER 32 AX UT IC</b>	
	Weight [kg]:	7.920
	Notation:	offset
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Center distance [mm]:	100
<b>8 033 46 192</b>	<b>Radial drilling and milling head ER 32 AX UT</b>	
	Weight [kg]:	7.430
	Notation:	offset
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	2:1
	Torque max [Nm]:	63
	Rotation max [1/min]:	3000
	Rotating direction:	same
	Coolant:	EXT
	Center distance [mm]:	100
<b>8 033 47 005</b>	<b>Radial drilling and milling head HT 5</b>	
	Weight [kg]:	7.480
	Notation:	offset
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	HT 5
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same

Part-#	Name	
	Coolant:	EXT
	Center distance [mm]:	100
<b>8 033 47 007</b>	<b>Radial drilling and milling head HT 5 IC</b>	
	Weight [kg]:	8.670
	Notation:	offset
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	HT 5
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Please note:	stronger bearing
	Center distance [mm]:	100
<b>8 033 47 008</b>	<b>Radial drilling and milling head ER 40</b>	
	Weight [kg]:	7.600
	Notation:	offset
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 40
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
	Center distance [mm]:	100
<b>8 033 47 012</b>	<b>Radial drilling and milling head HT 5 IC</b>	
	Weight [kg]:	8.100
	Notation:	offset
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	HT 5
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Center distance [mm]:	100
<b>8 033 47 018</b>	<b>Radial drilling and milling head C 25</b>	
	Weight [kg]:	7.700
	Notation:	offset
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	DIN 6388 - C 25
	Gear ratio [i]:	1:1

Part-#	Name	
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
	Center distance [mm]:	100
<b>8 033 47 069</b>	<b>Radial drilling and milling head HT 5 IC</b>	
	Notation:	offset
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	HT 5
	Gear ratio [i]:	1:2
	Torque max [Nm]:	16
	Rotation max [1/min]:	12000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Please note:	stronger bearing
	Center distance [mm]:	100
<b>8 033 48 002</b>	<b>Radial drilling and milling head HT 6</b>	
	Notation:	offset
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	HT 6
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	stronger bearing
	Center distance [mm]:	100
<b>8 037 49 019</b>	<b>Radial disk mill head shaft diameter 16-32</b>	
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Interchangeable arbor
	Gear ratio [i]:	3:1
	Torque max [Nm]:	80
	Rotation max [1/min]:	2000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	Price without arbor, strong version
	Center distance [mm]:	113
	Offset [mm]:	58

Part-#	Name	
<b>8 039 42 002</b>	<b>Radial drilling and milling head Weldon 6</b>	
	Weight [kg]:	6.220
	Version:	left
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Weldon (DIN 1835 b) 6 special
	Gear ratio [i]:	1:1
	Torque max [Nm]:	10
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	Special version
	Center distance [mm]:	185
<b>8 039 42 003</b>	<b>Radial drilling and milling head Weldon 6</b>	
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Weldon (DIN 1835 b) 6 special
	Gear ratio [i]:	1:1
	Torque max [Nm]:	10
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	Special version
	Center distance [mm]:	185
<b>8 039 43 000</b>	<b>Radial drilling and milling head Weldon 8</b>	
	Weight [kg]:	6.260
	Version:	left
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Weldon (DIN 1835 b) 8 special
	Gear ratio [i]:	1:1
	Torque max [Nm]:	10
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	Special version
	Center distance [mm]:	185
<b>8 039 43 001</b>	<b>Radial drilling and milling head Weldon 8</b>	
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Weldon (DIN 1835 b) 8 special
	Gear ratio [i]:	1:1
	Torque max [Nm]:	10
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	Special version
	Center distance [mm]:	209


Part-#	Name	
<b>8 039 46 044</b>	<b>Radial drilling and milling head ER 32 AX UT</b>	
	Weight [kg]:	8.490
	Notation:	offset in Y-axis
	Version:	Special
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
	Center distance [mm]:	115
<b>8 039 47 021</b>	<b>Radial drilling and milling head HT 5 IC</b>	
	Notation:	10° angle
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	HT 5
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	140
<b>8 039 47 022</b>	<b>Radial drilling and milling head HT 5 IC</b>	
	Notation:	15° angle
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	HT 5
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	140
<b>8 040 45 029</b>	<b>Universal head ±110° adjustable ER 25</b>	
	Weight [kg]:	6.420
	Version:	Special
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 25
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	Note length
	Center distance [mm]:	104

Part-#	Name	
<b>8 040 45 064</b>	<b>Universal head ± 90° adjustable ER 25 AX UT</b>	
	Weight [kg]:	5.110
	Version:	right
	Tool drive:	DIN 5482
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 25 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	stronger bearing
	Center distance [mm]:	87
<b>8 200 40 000</b>	<b>Plug Z2-40 K</b>	
	Weight [kg]:	0.140
	Shank size [mm]:	40.00
	Shank type:	VDI
<b>8 200 40 001</b>	<b>Plug Z2-40 S</b>	
	Weight [kg]:	1.360
	Shank size [mm]:	40.00
	Shank type:	VDI
<b>8 200 41 002</b>	<b>Tool holder A2-40x120</b>	
	Weight [kg]:	5.800
	Shank size [mm]:	40.00
	Shank type:	VDI
<b>8 200 41 003</b>	<b>Tool holder A2-40x200</b>	
	Weight [kg]:	9.120
	Shank size [mm]:	40.00
	Shank type:	VDI
<b>8 200 41 004</b>	<b>Tool holder A2-40x320</b>	
	Weight [kg]:	14.360
	Shank size [mm]:	40.00
	Shank type:	VDI
<b>8 200 44 000</b>	<b>Tool holder A1-40x100</b>	
	Weight [kg]:	11.940
	Shank size [mm]:	40.00
	Shank type:	VDI
<b>8 202 43 000</b>	<b>Basic holder transversal set SZ 40</b>	
	Weight [kg]:	1.560
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Interface SZ 40
	Coolant:	EXT

Part-#	Name	
<b>8 206 42 000</b>	<b>Adapter for VDI 30</b>	
	Weight [kg]:	3.530
	Version:	doubletoothed
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	DIN 69880 - 30
	Coolant:	EXT
	Please note:	Special
<b>8 208 49 001</b>	<b>Test mandrel VDI 40x40x200</b>	
	Weight [kg]:	3.020
	Shank size [mm]:	40.00
	Shank type:	VDI
<b>8 208 49 003</b>	<b>Test mandrel VDI 40x40x300</b>	
	Weight [kg]:	4.020
	Shank size [mm]:	40.00
	Shank type:	VDI
<b>8 210 41 000</b>	<b>Tool holder F 40-MK 1</b>	
	Weight [kg]:	1.600
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	DIN 228 D - MK 1
	Coolant:	IC
<b>8 210 42 001</b>	<b>Tool holder F 40-MK 2</b>	
	Weight [kg]:	1.620
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	DIN 228 D - MK 2
	Coolant:	IC
<b>8 210 43 000</b>	<b>Tool holder E2-40x 8</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 8
	Coolant:	IC/Ext
<b>8 210 43 002</b>	<b>Tool holder F 40-MK 3</b>	
	Weight [kg]:	1.520
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	DIN 228 D - MK 3
	Coolant:	IC
<b>8 210 43 003</b>	<b>Short drill chuck VDI 40x 8</b>	
	Weight [kg]:	1.700
	Shank size [mm]:	40.00
	Shank type:	VDI
	Coolant:	EXT
<b>8 210 43 004</b>	<b>Short drill chuck VDI 40x 8 - IC</b>	
	Weight [kg]:	1.730
	Shank size [mm]:	40.00
	Shank type:	VDI
	Coolant:	IC

Part-#	Name	
<b>8 210 44 001</b>	<b>Tool holder E2-40x10</b>	
	Weight [kg]:	2.320
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 10
	Coolant:	IC/Ext
<b>8 210 44 007</b>	<b>Tool holder F 40-MK 4</b>	
	Weight [kg]:	2.460
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	DIN 228 D - MK 4
	Coolant:	IC
<b>8 210 44 008</b>	<b>Short drill chuck VDI 40x13</b>	
	Weight [kg]:	2.280
	Shank size [mm]:	40.00
	Shank type:	VDI
	Coolant:	EXT
<b>8 210 44 009</b>	<b>Tool holder E2-40x14</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 14
	Coolant:	IC/Ext
<b>8 210 44 010</b>	<b>Tool holder E1-40x10</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 10
	Coolant:	IC
<b>8 210 44 011</b>	<b>Tool holder E1-40x12</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 12
	Coolant:	IC
<b>8 210 44 014</b>	<b>Short drill chuck VDI 40x13 - IC</b>	
	Weight [kg]:	2.290
	Shank size [mm]:	40.00
	Shank type:	VDI
	Coolant:	IC
<b>8 210 44 017</b>	<b>Tool holder E1-40x14</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 14
	Coolant:	IC
<b>8 210 44 019</b>	<b>Tool holder E2-40x10 - special</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 10
	Coolant:	IC/Ext
	Please note:	Shaft with hole, locked with screw

Part-#	Name	
<b>8 210 44 020</b>	<b>Tool holder E2-40x12 - special</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 12
	Coolant:	IC/Ext
	Please note:	Shaft with hole, locked with screw
<b>8 210 45 000</b>	<b>Tool holder E2-40x16</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 16
	Coolant:	IC/Ext
<b>8 210 45 002</b>	<b>Tool holder E4-40xER 25</b>	
	Weight [kg]:	1.570
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 25
	Coolant:	IC
<b>8 210 45 003</b>	<b>Tool holder E1-40x16</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 16
	Coolant:	IC
<b>8 210 45 006</b>	<b>Short drill chuck VDI 40x16</b>	
	Weight [kg]:	2.460
	Shank size [mm]:	40.00
	Shank type:	VDI
	Coolant:	EXT
<b>8 210 45 007</b>	<b>Tool holder E3-40x C 16</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	DIN 6388 - C 16
	Coolant:	IC
<b>8 210 45 009</b>	<b>Short drill chuck VDI 40x16 - IC</b>	
	Weight [kg]:	2.320
	Shank size [mm]:	40.00
	Shank type:	VDI
	Coolant:	IC
<b>8 210 45 013</b>	<b>Tool holder E2-40x18</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 18
	Coolant:	IC/Ext
<b>8 210 45 014</b>	<b>Tool holder E1-40x18</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 18
	Coolant:	IC

Part-#	Name	
<b>8 210 45 020</b>	<b>Tool holder ER 25 AX UT IC</b>	
	Weight [kg]:	1.860
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 25 A - u-tec
	Coolant:	IC/Ext
<b>8 210 46 000</b>	<b>Tool holder E4-40xER 32</b>	
	Weight [kg]:	1.640
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32
	Coolant:	IC
<b>8 210 46 002</b>	<b>Tool holder E2-40x20</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 20
	Coolant:	IC/Ext
<b>8 210 46 004</b>	<b>Tool holder E1-40x20</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 20
	Coolant:	IC
<b>8 210 46 010</b>	<b>Tool holder E2-40x20 - special</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 20
	Coolant:	IC/Ext
	Please note:	Shaft with hole, locked with screw
<b>8 210 47 001</b>	<b>Tool holder E2-40x25</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 25
	Coolant:	IC/Ext
<b>8 210 47 003</b>	<b>Tool holder E3-40x C 25</b>	
	Weight [kg]:	1.980
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	DIN 6388 - C 25
	Coolant:	IC
<b>8 210 47 004</b>	<b>Tool holder E4-40xER 40</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 40
	Coolant:	IC



Part-#	Name	
<b>8 210 47 005</b>	<b>Tool holder E1-40x25</b>	
	Weight [kg]:	1.840
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 25
	Coolant:	IC
<b>8 210 48 001</b>	<b>Tool holder E2-40x32</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 32
	Coolant:	IC/Ext
<b>8 210 48 003</b>	<b>Tool holder E3-40x C 32</b>	
	Weight [kg]:	2.480
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	DIN 6388 - C 32
	Coolant:	IC
<b>8 210 48 004</b>	<b>Tool holder E1-40x32</b>	
	Weight [kg]:	1.830
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 32
	Coolant:	IC
<b>8 210 48 012</b>	<b>Tool holder E2-40x32 special</b>	
	Version:	Special
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 32
	Coolant:	IC/Ext
	Please note:	with end stop
<b>8 210 49 000</b>	<b>Tool holder E2-40x40</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 40
	Coolant:	IC/Ext
<b>8 210 49 002</b>	<b>Tool holder E1-40x40</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 40
	Coolant:	IC
<b>8 210 49 003</b>	<b>Tool holder E1-40x50</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 50
	Coolant:	IC

Gildemeister  
 CTX 510 ECO line DIN 5482

Part-#	Name	
	<b>8 210 49 005 Tool holder E2-40x50</b>	
	Weight [kg]:	3.000
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 50
	Coolant:	IC/Ext
	<b>8 214 43 000 Tool holder C1-40x25</b>	
	Employment for:	VDI 40
	Version:	right
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Sq. 25/20
	Coolant:	EXT
	<b>8 214 43 001 Tool holder C3-40x25</b>	
	Employment for:	VDI 40
	Version:	right
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Sq. 25/20
	Coolant:	EXT
	<b>8 214 43 008 Tool holder C1-40x25 special</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Sq. 25/20
	Coolant:	EXT
	<b>8 219 47 004 Boring bar holder ø 25</b>	
	Weight [kg]:	2.820
	Version:	left; offset
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 25
	Coolant:	IC/Ext
Offset [mm]:	25	
	<b>8 219 48 006 Boring bar holder ø 32</b>	
	Version:	left, offset
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Ø 32
	Coolant:	IC/Ext
	Offset [mm]:	30
	<b>8 234 43 000 Tool holder B1-40x25x44</b>	
	Employment for:	VDI 40
	Version:	right
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Sq. 25/20
	Coolant:	EXT

Part-#	Name	
<b>8 234 43 001</b>	<b>Tool holder B3-40x25x44</b>	
	Employment for:	VDI 40
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Sq. 25/20
	Coolant:	EXT
<b>8 234 43 002</b>	<b>Tool holder B5-40x25x44</b>	
	Weight [kg]:	3.120
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Sq. 25/20
	Coolant:	EXT
<b>8 234 43 003</b>	<b>Tool holder B7-40x25x44</b>	
	Weight [kg]:	3.320
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Sq. 25/20
	Coolant:	EXT
<b>8 234 43 005</b>	<b>Tool holder B5-40x25x44 special</b>	
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Sq. 25/20
	Coolant:	EXT
<b>8 262 49 000</b>	<b>Stock stop VDI 40 - Ø 42</b>	
	Weight [kg]:	1.360
	Shank size [mm]:	40.00
	Shank type:	VDI
<b>8 262 49 001</b>	<b>Stock stop VDI 40 - Ø 60</b>	
	Weight [kg]:	1.620
	Shank size [mm]:	40.00
	Shank type:	VDI
<b>8 262 49 002</b>	<b>Stock stop VDI 40 - Ø 54</b>	
	Weight [kg]:	1.530
	Shank size [mm]:	40.00
	Shank type:	VDI
<b>8 267 49 001</b>	<b>Bar pick-up VDI 40 offset</b>	
	Weight [kg]:	2.100
	Version:	right
	Shank size [mm]:	40.00
	Shank type:	VDI
	Please note:	Chuck jaws 62-85 mm special accessories
<b>8 274 43 000</b>	<b>Square multiple holder D1-40x25</b>	
	Weight [kg]:	3.660
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Sq. 25/20
	Coolant:	EXT

Gildemeister  
 CTX 510 ECO line DIN 5482

Part-#	Name	
<b>8 274 43 001</b>	<b>Tool holder D2-40x25</b>	
	Weight [kg]:	4.300
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Sq. 25/20
	Coolant:	EXT
<b>8 320 42 018</b>	<b>Cut-off holder, height adjustable SH 26 IC</b>	
	Version:	universal
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Clampshaft SH 26
	Coolant:	IC/Ext
	Pressure max [bar]:	70
<b>8 320 43 009</b>	<b>Cut-off holder, height adjustable SH 32 IC</b>	
	Weight [kg]:	2.480
	Version:	universal
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	Clampshaft SH 32
	Coolant:	IC/Ext
	Pressure max [bar]:	70
<b>8 320 49 005</b>	<b>Cut-off holder, height adjustable 845 IC</b>	
	Weight [kg]:	2.700
	Version:	universal
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	 System 845
	Coolant:	IC
	Pressure max [bar]:	70
<b>8 742 41 000</b>	<b>Clamping ring Z1- VDI 40</b>	
	Weight [kg]:	0.580
	Shank type:	VDI
	Coolant:	EXT



● heimatec overseas branches

○ global representations of heimatec

**heimatec**<sup>®</sup>

**heimatec GmbH**  
Präzisionswerkzeuge  
Carl-Benz-Str. 4  
77871 Renchen  
Germany

T +49 7843 9466 0  
[www.heimatec.com](http://www.heimatec.com)  
[info@heimatec.com](mailto:info@heimatec.com)

Please find the contact details of our worldwide trading partners on our website:  
<https://heimatec.com/business-partners>