

TOPSELLER -
many more available!

Live Tools


heimatec®

SPINNER


TS 750 - BMT 65

Part-#	Tool adaption	Rotation max [1/min]	Gear ratio	Coolant	Pressure max.	Center distance
Axial drilling and milling head						
8 010 66 143	ER 32 A - u-tec	12.000	1:1	IC/Ext	100 bar	--
8 010 66 145	ER 32 A - u-tec	12.000	1:1	EXT	140 bar	--
Radial drilling and milling head						
8 030 66 269	ER 32 A - u-tec	10.000	1:1	EXT	--	100 mm
Radial drilling and milling head, double spindle						
8 039 66 021	ER 32 A - u-tec	10.000	1:1	EXT	--	100 mm
Universal head, offset						
8 043 65 000	ER 25 A - u-tec	6.000	1:1	EXT	--	69 mm


Illustrations similar.




8 010 66 143




8 010 66 145



8 030 66 269



8 039 66 021



8 043 65 000

TOPSELLER -
many more available!

Static Tools

heimatec®

SPINNER

TS 750 - BMT 65

Part-#	Tool adaption	Coolant	Pressure max.
Multiple boring bar holder			
8 253 18 023	Ø 32	IC/Ext	140 bar
Multiple boring bar holder, double			
8 259 18 000	Ø 32	IC/Ext	140 bar

Illustrations similar.



8 253 18 023



8 259 18 000