

TOPSELLER -
many more available!

Live Tools


heimatec®

Nakamura

SC-200 II - 16 Stationen

Part-#	Tool adaption	Rotation max [1/min]	Gear ratio	Coolant	Pressure max.	Center distance
Axial drilling and milling head						
8 010 56 151	ER 32 A - u-tec	12.000	1:1	EXT	--	--
8 010 56 153	ER 32 A - u-tec	15.000	1:1	IC/Ext	100 bar	--
Radial drilling and milling head						
8 030 56 235	ER 32 A - u-tec	12.000	1:1	EXT	--	65 mm
Radial drilling and milling head, double spindle						
8 039 55 047	ER 25 A - u-tec	12.000	1:1	EXT	--	75 mm
8 039 56 016	ER 32 A - u-tec	12.000	1:1	EXT	--	65 mm
8 039 56 021	ER 32 A - u-tec	12.000	1:1	EXT	--	75 mm
Universal head						
8 040 54 032	ER 16 A - u-tec	12.000	1:1	EXT	140 bar	46 mm
Universal head, offset						
8 043 54 000	ER 16 A - u-tec	6.000	1:1	EXT	--	69 mm
8 043 54 001	ER 16 A - u-tec	6.000	1:1	IC/Ext	140 bar	69 mm


Illustrations similar.




8 010 56 151




8 010 56 153




8 030 56 235



8 039 55 047



8 040 54 032



8 043 54 000

TOPSELLER -
many more available!

Static Tools

heimatec®

Nakamura

SC-200 II - 16 Stationen

Part-#	Tool adaption	Coolant	Pressure max.	Center distance
Universal turning holder				
8 224 15 002	Sq. 25	EXT	--	--
8 224 15 062	Sq. 25	IC/Ext	140 bar	--
Boring bar holder				
8 240 17 005	Ø 25	IC/Ext	--	75 mm
8 240 19 009	Ø 40	IC/Ext	140 bar	75 mm
Double turning holder				
8 251 15 048	Sq. 25	IC/Ext	100 bar	--

Illustrations similar.




8 224 15 002



8 224 15 062



8 240 17 005



8 251 15 048