TOOL CATALOGUE

heimatec®

Nakamura

# JX-250 Ø65/75 Std. Revolver rechts

11/2026




# High-tech from heimatec -
# heimatec - Tools and systems for productive turning and milling

heimatec belongs to the international technology and quality leaders for precision tools and specializes in the development and production of high-precision static and live tools for all CNC lathes, CNC turn-/mill machines and CNC machining centers.

The range of products* spans from static BMT and VDI tool holders, live tools up to highly complex customer-specific individual solutions. heimatec, headquartered in Renchen, has a own subsiiary in Asia and India and numerous representatives as well as trading partners all over the world.

## *OUR PRODCUTS


Static tool holders
Live tool units
Precision tools
Tools for turning and machining centres
Tools for swiss type lathes
Tool changing and uick-change systems
Tool systems for gear production
Digital tool management

This catalogue, including all its parts, is protected by copyright. Any use outside the restricted limitations of the Copyright Act without the consent of heimatec is inadmissible and liable to prosecution. This applies in particular to duplication, translation, microfilming and storage and processing in electronic systems.

**heimatec GmbH** reserves the right to make technical changes at any time without giving prior notice. This applies in particular to adjustments at any time to meet new or changed international standards, or in case of further developments of our products or manufacturing processes.

The current version of our General Terms and Conditions can be found on our website.

# JX-250 Ø65/75 Std. Revolver rechts




| Part-# | Name | |
|---|---|---|
| **8 010 55 033** | **Axial milling and drill holder ER 25 AX UT** | |
|  | Weight [kg]: | 2.830 |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Please note: | Combi bearing |
| **8 010 55 109** | **Axial drilling and milling head ER 25 AX UT** | |
|  | Weight [kg]: | 2.600 |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| **8 010 55 111** | **Axial drilling and milling head ER 25 AX UT IC** | |
|  | Weight [kg]: | 3.000 |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 15000 |
| | Rotating direction: | same |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 100 |
| | Please note: | Dryrun possible |
| **8 010 56 031** | **Axial drilling and milling head HT 4 IC** | |
|  | Weight [kg]: | 1.760 |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | HT 4 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | same |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 25 |
| | Please note: | short version |

© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts

| Part-# | Name | |
|---|---|---|
| **8 010 56 032** | **Axial drilling and milling head HT 4** | |
|  | Weight [kg]: | 1.740 |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | HT 4 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Please note: | short version |
| **8 010 56 063** | **Axial milling and drill holder ER 32 AX UT** | |
|  | Weight [kg]: | 3.000 |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 32 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Please note: | Combi bearing |
| **8 010 56 110** | **Axial drilling and milling head C 4** | |
|  | Weight [kg]: | 4.750 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | heimatec Capto(TM) C 4 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Please note: | Check applicability; tool length check ! |
| **8 010 56 111** | **Axial drilling and milling head C 4 IC** | |
|  | Weight [kg]: | 5.800 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | heimatec Capto(TM) C 4 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | same |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 100 |
| | Please note: | Check applicability; tool length check ! |


© heimatec GmbH • Subject to technical changes.


heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts

| Part-# | Name |
|---|---|

**8 010 56 120** **Axial drilling and milling head C 4 IC**



| | |
|---|---|
| Notation: | 180° reversible |
| Tool drive: | Flat (~DIN 1809) |
| Shank size [mm]: | 55.00 |
| Shank type: | BMT |
| Machine adaption: | Centering key b 20 |
| Tool adaption: | heimatec Capto(TM) C 4 |
| Gear ratio [i]: | 1:1 |
| Torque max [Nm]: | 50 |
| Rotation max [1/min]: | 6000 |
| Rotating direction: | same |
| Coolant: | IC/Ext |
| Pressure max [bar]: | 25 |
| Please note: | Check applicability; tool length check ! |

**8 010 56 140** **Axial drilling and milling head ER 32 AX UT IC**



| | |
|---|---|
| Weight [kg]: | 3.000 |
| Tool drive: | Flat (~DIN 1809) |
| Shank size [mm]: | 55.00 |
| Shank type: | BMT |
| Tool adaption: | ER 32 A - u-tec |
| Gear ratio [i]: | 1:1 |
| Torque max [Nm]: | 50 |
| Rotation max [1/min]: | 6000 |
| Rotating direction: | same |
| Coolant: | IC/Ext |
| Pressure max [bar]: | 100 |

**8 010 56 144** **Axial drilling and milling head HT 4 IC**



| | |
|---|---|
| Tool drive: | Flat (~DIN 1809) |
| Shank size [mm]: | 55.00 |
| Shank type: | BMT |
| Tool adaption: | HT 4 |
| Gear ratio [i]: | 1:1 |
| Torque max [Nm]: | 50 |
| Rotation max [1/min]: | 6000 |
| Rotating direction: | same |
| Coolant: | IC/Ext |
| Pressure max [bar]: | 100 |

**8 010 56 151** **Axial drilling and milling head ER 32 AX UT**



| | |
|---|---|
| Weight [kg]: | 2.770 |
| Tool drive: | Flat (~DIN 1809) |
| Shank size [mm]: | 55.00 |
| Shank type: | BMT |
| Tool adaption: | ER 32 A - u-tec |
| Gear ratio [i]: | 1:1 |
| Torque max [Nm]: | 50 |
| Rotation max [1/min]: | 12000 |
| Rotating direction: | same |
| Coolant: | EXT |

© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts

| Part-# | Name | |
|---|---|---|
| **8 010 56 153** | **Axial drilling and milling head ER 32 AX UT IC** | |
|  | Weight [kg]: | 3.180 |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 32 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 15000 |
| | Rotating direction: | same |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 100 |
| **8 011 54 006** | **Axial milling head universal arbor 3/4"** | |
|  | Weight [kg]: | 2.910 |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | Universal arbor 3/4" (19,05mm) |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Please note: | Combi bearing |
| **8 011 55 015** | **Axial milling head universal arbor 22** | |
|  | Weight [kg]: | 3.000 |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | Universal arbor 22 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Please note: | Combi bearing |
| **8 013 54 005** | **Axial drilling and milling head ER 16 AX UT** | |
|  | Weight [kg]: | 2.200 |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:4 |
| | Torque max [Nm]: | 5 |
| | Rotation max [1/min]: | 24000 |
| | Rotating direction: | same |
| | Coolant: | EXT |


© heimatec GmbH • Subject to technical changes.


heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts

| Part-# | Name |
|---|---|

**8 013 54 007** **Axial drilling and milling head ER 16 AX UT IC**




| | |
|---|---|
| Tool drive: | Flat (~DIN 1809) |
| Shank size [mm]: | 55.00 |
| Shank type: | BMT |
| Tool adaption: | ER 16 A - u-tec |
| Gear ratio [i]: | 1:4 |
| Torque max [Nm]: | 5 |
| Rotation max [1/min]: | 24000 |
| Rotating direction: | same |
| Coolant: | IC/Ext |
| Pressure max [bar]: | 80 |

**8 019 54 055** **Axial drilling and milling head ER 16 M IC**




| | |
|---|---|
| Weight [kg]: | 6.200 |
| Notation: | offset; 180° reversible |
| Tool drive: | Flat (~DIN 1809) |
| Shank size [mm]: | 55.00 |
| Shank type: | BMT |
| Tool adaption: | ER 16 M |
| Gear ratio [i]: | 1:2 |
| Torque max [Nm]: | 25 |
| Rotation max [1/min]: | 12000 |
| Rotating direction: | opposite |
| Coolant: | IC/Ext |
| Pressure max [bar]: | 140 |
| Please note: | stronger bearing |
| Offset [mm]: | 42 |

**8 019 55 018** **Axial drilling and milling head ER 25 AX UT**



| | |
|---|---|
| Weight [kg]: | 5.230 |
| Notation: | offset; 180° reversible |
| Tool drive: | Flat (~DIN 1809) |
| Shank size [mm]: | 55.00 |
| Shank type: | BMT |
| Tool adaption: | ER 25 A - u-tec |
| Gear ratio [i]: | 1:1 |
| Torque max [Nm]: | 40 |
| Rotation max [1/min]: | 6000 |
| Rotating direction: | opposite |
| Coolant: | EXT |
| Please note: | stronger bearing |
| Offset [mm]: | 42 |

**8 019 55 023** **Axial drilling and milling head ER 25 AX UT IC**







| | |
|---|---|
| Weight [kg]: | 6.260 |
| Notation: | offset; 180° reversible |
| Tool drive: | Flat (~DIN 1809) |
| Shank size [mm]: | 55.00 |
| Shank type: | BMT |
| Tool adaption: | ER 25 A - u-tec |
| Gear ratio [i]: | 1:1 |
| Torque max [Nm]: | 40 |
| Rotation max [1/min]: | 6000 |
| Rotating direction: | opposite |
| Coolant: | IC/Ext |
| Pressure max [bar]: | 140 |

© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts




| Part-# | Name | |
|---|---|---|
| | Please note: | stronger bearing |
| | Offset [mm]: | 42 |
| **8 019 55 024** | **Axial drilling and milling head ER 25 AX UT** | |
|  | Weight [kg]: | 5.230 |
| | Notation: | offset; 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 25 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Please note: | stronger bearing |
| | Offset [mm]: | 42 |
| **8 019 55 025** | **Axial drilling and milling head ER 25 AX UT IC** | |
|  | Weight [kg]: | 6.330 |
| | Notation: | offset; 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 25 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | opposite |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | stronger bearing |
| | Offset [mm]: | 42 |
| **8 019 55 026** | **Axial drilling and milling head ER 25 AX UT** | |
|  | Weight [kg]: | 5.300 |
| | Notation: | offset; 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:3 |
| | Torque max [Nm]: | 16 |
| | Rotation max [1/min]: | 18000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Please note: | stronger bearing |
| | Offset [mm]: | 42 |
| **8 019 55 027** | **Axial drilling and milling head ER 25 AX UT IC** | |
|  | Weight [kg]: | 6.350 |
| | Notation: | offset; 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |


© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts



| Part-# | Name | |
|---|---|---|
| | Gear ratio [i]: | 1:3 |
| | Torque max [Nm]: | 16 |
| | Rotation max [1/min]: | 18000 |
| | Rotating direction: | opposite |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | stronger bearing |
| | Offset [mm]: | 42 |
| **8 019 55 028** | **Axial drilling and milling head ER 25 AX UT** | |
|  | Weight [kg]: | 5.240 |
| | Notation: | offset; 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 2:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 3000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Please note: | stronger bearing |
| | Offset [mm]: | 42 |
| **8 019 55 029** | **Axial drilling and milling head ER 25 AX UT IC** | |
|  | Weight [kg]: | 6.220 |
| | Notation: | offset; 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 2:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 3000 |
| | Rotating direction: | opposite |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | stronger bearing |
| | Offset [mm]: | 42 |
| **8 019 56 042** | **Axial drilling and milling head C 4 IC** | |
|  | Weight [kg]: | 7.720 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | heimatec Capto(TM) C 4 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | opposite |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | Check applicability; note tool length! |
| | Offset [mm]: | 62 |

© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts



| Part-# | Name | |
|---|---|---|
| **8 019 56 057** | **Axial drilling and milling head C 4 IC** | |
|  | Weight [kg]: | 7.650 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | heimatec Capto(TM) C 4 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | opposite |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | Check applicability; note tool length! |
| | Offset [mm]: | 62 |
| **8 030 55 076** | **Angle-mill- and drill holder ER 25 AX UT** | |
| | Weight [kg]: | 6.860 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Please note: | Combi bearing |
| | Center distance [mm]: | 75 |
| **8 030 55 081** | **Angle-mill- and drill holder ER 25 AX UT IC** | |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | opposite |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | Combi bearing |
| | Center distance [mm]: | 75 |
| **8 030 55 122** | **Radial drilling and milling head ER 25 AX UT** | |
|  | Weight [kg]: | 6.380 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 16 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |


© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts


| Part-# | Name | |
|---|---|---|
| | Coolant: | EXT |
| | Please note: | stronger bearing; check applicability; |
| | Center distance [mm]: | 77 |
| **8 030 55 123** | **Radial drilling and milling head ER 25 AX UT IC** | |
|  | Weight [kg]: | 6.550 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 16 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | stronger bearing |
| | Center distance [mm]: | 77 |
| **8 030 55 139** | **Radial drilling and milling head ER 25 AX UT IC** | |
|  | Weight [kg]: | 6.560 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:3 |
| | Torque max [Nm]: | 12 |
| | Rotation max [1/min]: | 18000 |
| | Rotating direction: | same |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | stronger bearing |
| | Center distance [mm]: | 77 |
| **8 030 55 140** | **Radial drilling and milling head ER 25 AX UT** | |
| | Weight [kg]: | 6.700 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:3 |
| | Torque max [Nm]: | 12 |
| | Rotation max [1/min]: | 18000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Please note: | stronger bearing |
| | Center distance [mm]: | 77 |

© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts



| Part-# | Name | |
|---|---|---|
| **8 030 55 240** | **Radial drilling and milling head ER 25 AX UT** | |
|  | Weight [kg]: | 6.380 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Center distance [mm]: | 75 |
| **8 030 55 241** | **Angle drilling and milling head ER 25 AX UT IC** | |
|  | Weight [kg]: | 6.960 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | opposite |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Center distance [mm]: | 75 |
| **8 030 56 076** | **Radial drilling and milling head HT 4** | |
| | Weight [kg]: | 6.970 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | HT 4 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Please note: | Combi bearing |
| | Center distance [mm]: | 75 |
| **8 030 56 077** | **Radial drilling and milling head HT 4** | |
| | Weight [kg]: | 6.920 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | HT 4 |
| | Gear ratio [i]: | 2:1 |
| | Torque max [Nm]: | 63 |
| | Rotation max [1/min]: | 3000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Please note: | Combi bearing |


© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts

| Part-# | Name | |
|---|---|---|
| | Center distance [mm]: | 75 |
| **8 030 56 087** | **Angle-mill- and drill holder ER 32 AX UT** | |
|  | Weight [kg]: | 6.880 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 32 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Please note: | Combi bearing |
| | Center distance [mm]: | 75 |
| **8 030 56 088** | **Angle-mill- and drill holder ER 32 AX UT IC** | |
|  | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 32 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | opposite |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | Combi bearing |
| | Center distance [mm]: | 75 |
| **8 030 56 092** | **Radial drilling and milling head ER 32 AX UT** | |
|  | Weight [kg]: | 6.830 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 32 A - u-tec |
| | Gear ratio [i]: | 2:1 |
| | Torque max [Nm]: | 63 |
| | Rotation max [1/min]: | 3000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Please note: | Combi bearing |
| | Center distance [mm]: | 75 |
| **8 030 56 093** | **Radial drilling and milling head ER 32 AX UT IC** | |
| | Weight [kg]: | 7.040 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 32 A - u-tec |
| | Gear ratio [i]: | 2:1 |
| | Torque max [Nm]: | 63 |
| | Rotation max [1/min]: | 3000 |

© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts

| Part-# | Name | |
|---|---|---|
| | Rotating direction: | opposite |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | Combi bearing |
| | Center distance [mm]: | 75 |
| **8 030 56 107** | **Radial drilling and milling head HT 4 IC** | |
| | Weight [kg]: | 7.180 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | HT 4 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | opposite |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | Combi bearing |
| | Center distance [mm]: | 75 |
| **8 030 56 121** | **Radial drilling and milling head HT 4 IC** | |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | HT 4 |
| | Gear ratio [i]: | 1:3 |
| | Torque max [Nm]: | 12 |
| | Rotation max [1/min]: | 18000 |
| | Rotating direction: | same |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | stronger bearing |
| | Center distance [mm]: | 77 |
| **8 030 56 124** | **Radial drilling and milling head HT 4** | |
| | Weight [kg]: | 6.300 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | HT 4 |
| | Gear ratio [i]: | 1:3 |
| | Torque max [Nm]: | 12 |
| | Rotation max [1/min]: | 18000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Please note: | stronger bearing |
| | Center distance [mm]: | 77 |


© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts



| Part-# | Name | |
|---|---|---|
| **8 030 56 125** | **Radial drilling and milling head HT 4 IC** | |
| | Weight [kg]: | 6.520 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | HT 4 |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 16 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | stronger bearing |
| | Center distance [mm]: | 77 |
| **8 030 56 126** | **Radial drilling and milling head HT 4** | |
| | Weight [kg]: | 6.340 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | HT 4 |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 16 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Please note: | stronger bearing |
| | Center distance [mm]: | 77 |
| **8 030 56 237** | **Radial drilling and milling head ER 32 AX UT** | |
|  | Weight [kg]: | 6.500 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 32 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Center distance [mm]: | 75 |
| **8 030 56 238** | **Radial drilling and milling head ER 32 AX UT IC** | |
|  | Weight [kg]: | 7.200 |
| | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 32 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | opposite |
| | Coolant: | IC/Ext |

© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts




| Part-# | Name | |
|---|---|---|
| | Pressure max [bar]: | 140 |
| | Center distance [mm]: | 75 |
| **8 030 56 256** | **Radial drilling and milling head HT 4** | |
|  | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | HT 4 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | opposite |
| | Coolant: | EXT |
| | Center distance [mm]: | 75 |
| **8 030 56 257** | **Radial drilling and milling head HT 4 IC** | |
|  | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | HT 4 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | opposite |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Center distance [mm]: | 75 |
| **8 037 53 001** | **Radial disk mill head arbor 13** | |
| | Weight [kg]: | 6.960 |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | Arbor 13 |
| | Gear ratio [i]: | 2:1 |
| | Torque max [Nm]: | 32 |
| | Rotation max [1/min]: | 3000 |
| | Rotating direction: | opposite |
| | Coolant: | no |
| | Center distance [mm]: | 76 |
| **8 037 54 007** | **Radial disk mill head arbor 16** | |
| | Weight [kg]: | 12.220 |
| | Version: | ± 10° turnable; at 0° position can be pinned |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | Arbor 16 |
| | Gear ratio [i]: | 2:1 |
| | Torque max [Nm]: | 63 |
| | Rotation max [1/min]: | 3000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Please note: | strong version; stronger bearing |
| | Center distance [mm]: | 87,5 |


© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts



| Part-# | Name | |
|---|---|---|
| **8 037 55 007** | **Radial disk mill head arbor 22** | |
|  | Weight [kg]: | 12.520 |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | Arbor 22 |
| | Gear ratio [i]: | 2:1 |
| | Torque max [Nm]: | 63 |
| | Rotation max [1/min]: | 3000 |
| | Rotating direction: | same |
| | Coolant: | no |
| | Please note: | strong version with stronger bearing |
| | Center distance [mm]: | 87,5 |
| **8 037 55 013** | **Radial disk mill head arbor 1"** | |
| | Weight [kg]: | 11.640 |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | Arbor 1" (25,4mm) |
| | Gear ratio [i]: | 2:1 |
| | Torque max [Nm]: | 63 |
| | Rotation max [1/min]: | 3000 |
| | Rotating direction: | same |
| | Coolant: | no |
| | Please note: | strong version with stronger bearing |
| | Center distance [mm]: | 87,5 |
| **8 039 55 047** | **Radial drilling and milling head ER 25 AX UT** | |
|  | Weight [kg]: | 6.800 |
| | Notation: | 180° reversible |
| | Employment for: | Main- and sub spindle |
| | Version: | double spindle |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 25 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same/opposite |
| | Coolant: | EXT |
| | Please note: | stronger bearing |
| | Center distance [mm]: | 75 |
| **8 039 56 021** | **Radial drilling and milling head ER 32 AX UT** | |
|  | Weight [kg]: | 6.600 |
| | Notation: | 180° reversible |
| | Employment for: | Main- and sub spindle |
| | Version: | double spindle |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 32 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50 |
| | Rotation max [1/min]: | 12000 |

*© heimatec GmbH • Subject to technical changes.*

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts

| Part-# | Name | |
|---|---|---|
| | Rotating direction: | same/opposite |
| | Coolant: | EXT |
| | Please note: | stronger bearing |
| | Center distance [mm]: | 75 |
| **8 040 53 000** | **Universal head ± 90° adjustable ER 11 AX** | |
| | Weight [kg]: | 3.150 |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 11 A |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 10 |
| | Rotation max [1/min]: | 5000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Center distance [mm]: | 57 |
| **8 040 54 002** | **Universal head ± 90° adjustable ER 16** | |
|  | Weight [kg]: | 3.180 |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 10 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Center distance [mm]: | 57 |
| **8 040 54 032** | **Universal head ± 90° adjustable ER 16 AX UT** | |
|  | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 16 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Pressure max [bar]: | 140 |
| | Please note: | Check applicability; note center distance! |
| | Center distance [mm]: | 46 |
| **8 043 54 000** | **Universal head +135°/-30° adj. ER16 AX UT** | |
|  | Weight [kg]: | 9.850 |
| | Notation: | offset; 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 25 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | same |
| | Coolant: | EXT |


© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts


| Part-# | Name | |
|---|---|---|
| | Center distance [mm]: | 69 |
| | Offset [mm]: | 60 |
| **8 043 54 001** | **Universal head +135°/-30° adj. ER16AX UTIK** | |
| | Weight [kg]: | 9.920 |
| | Notation: | offset; 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 25 |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | same |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Center distance [mm]: | 69 |
| | Offset [mm]: | 60 |
| **8 043 54 002** | **Universal head +135°/-30° adj. ER16 AX UT** | |
| | Weight [kg]: | 9.930 |
| | Notation: | offset; 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 12 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Center distance [mm]: | 69 |
| | Offset [mm]: | 60 |
| **8 043 54 003** | **Universal head +135°/-30° adj. ER16AX UTIK** | |
| | Weight [kg]: | 9.900 |
| | Notation: | offset |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 12 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | 180° reversible |
| | Center distance [mm]: | 69 |
| | Offset [mm]: | 60 |
| **8 050 54 005** | **Multispindle drilling head ER 16 AX UT** | |
| | Weight [kg]: | 6.100 |
| | Notation: | offset |
| | Version: | 2-spindles |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |

© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts




| Part-# | Name | |
|---|---|---|
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:2 |
| | Torque max [Nm]: | 16 |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Offset [mm]: | 56 |
| **8 050 54 048** | **Multispindle drilling head ER 16 AX UT** | |
|  | Notation: | offset |
| | Version: | 2-spindles |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 25/Sp. |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Pressure max [bar]: | 140 |
| | Please note: | Check applicability! |
| | Offset [mm]: | 58 |
| **8 050 56 006** | **Multispindle drilling head C 4 IC** | |
| | Notation: | 180° reversible |
| | Employment for: | Main- and sub spindle |
| | Version: | 2-spindles |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | heimatec Capto(TM) C 4 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 50/Sp. |
| | Rotation max [1/min]: | 6000 |
| | Rotating direction: | opposite |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | Check applicability; tool length check ! |
| | Offset [mm]: | 62 |
| **8 053 54 045** | **Multispindle radial head ER 16 AX UT** | |
|  | Weight [kg]: | 6.850 |
| | Notation: | 180° reversible |
| | Version: | 2-spindles |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 32/Sp |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Center distance [mm]: | 75 |


© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts


| Part-# | Name | |
|---|---|---|
| **8 053 54 046** | **Multispindle radial head ER 16 AX UTIK** | |
|  | Notation: | 180° reversible |
| | Version: | 2-spindles |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 16 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 32/Sp |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Center distance [mm]: | 75 |
| **8 053 54 047** | **Multispindle radial head ER 20 AX UT** | |
|  | Notation: | 180° reversible |
| | Version: | 2-spindles |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 20 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 32/Sp |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Center distance [mm]: | 75 |
| **8 053 54 048** | **Multispindle radial head ER 20 AX UTIK** | |
|  | Notation: | 180° reversible |
| | Version: | 2-spindles |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | ER 20 A - u-tec |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 32/Sp |
| | Rotation max [1/min]: | 12000 |
| | Rotating direction: | same |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Center distance [mm]: | 75 |
| **8 068 54 000** | **Radial whirling unit HW 46** | |
|  | Notation: | 180° reversible |
| | Tool drive: | Flat (~DIN 1809) |
| | Shank size [mm]: | 55.00 |
| | Shank type: | BMT |
| | Tool adaption: | HW 46 |
| | Gear ratio [i]: | 1:1 |
| | Torque max [Nm]: | 16 |
| | Rotation max [1/min]: | 8000 |
| | Rotating direction: | same |
| | Coolant: | EXT |
| | Please note: | without cutting inserts carrier; check applicability; |

© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts



| Part-# | Name | |
|---|---|---|
| | Center distance [mm]: | 65 |
| **8 200 03 002** | **Cover plate** | |
|  | Weight [kg]: | 0.300 |
| | Shank type: | BMT |
| **8 224 11 003** | **Cut-off holder sq. 20** | |
| | Weight [kg]: | 1.040 |
| | Employment for: | right cutting tools |
| | Version: | Edge on side of turret |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 20 |
| | Coolant: | EXT |
| **8 224 11 005** | **Cut-off holder sq. 20** | |
| | Weight [kg]: | 1.100 |
| | Employment for: | left cutting tools |
| | Version: | Edge on center of turret |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 20 |
| | Coolant: | EXT |
| **8 224 11 016** | **Cut-off holder sq. 3/4" R 1441** | |
| | Weight [kg]: | 1.110 |
| | Employment for: | right cutting tools |
| | Version: | Edge on side of turret |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 3/4" (19,05mm) |
| | Coolant: | EXT |
| **8 224 11 022** | **Cut-off holder sq. 20** | |
|  | Weight [kg]: | 1.350 |
| | Employment for: | right cutting tools |
| | Version: | Edge on side of turret |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 20 |
| | Coolant: | EXT |
| **8 224 13 004** | **Cut-off holder SH 32** | |
| | Weight [kg]: | 1.000 |
| | Employment for: | Cut-off tool 32 |
| | Version: | Clampshaft on turret center |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Clampshaft SH 32 |
| | Coolant: | EXT |


© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts

| Part-# | Name | |
|---|---|---|
| **8 224 13 007** | **Cut-off holder SH 32** | |
|  | Weight [kg]: | 1.190 |
| | Employment for: | Cut-off tool 32 |
| | Version: | Clampshaft on turret side |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Clampshaft SH 32 |
| | Coolant: | EXT |
| **8 224 15 002** | **Universal turning holder sq. 25/20** | |
|  | Weight [kg]: | 2.800 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 25<br>Sq. 25 |
| | Coolant: | EXT |
| | Please note: | With spacer strip for sq. 20 |
| **8 224 15 012** | **Universal turning holder sq. 1"** | |
| | Weight [kg]: | 2.720 |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 1" (25,4mm)<br>Sq. 1" (25,4mm) |
| | Coolant: | EXT |
| **8 224 15 062** | **Universal turning holder sq. 25 IC** | |
|  | Weight [kg]: | 3.100 |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 25<br>Sq. 25 |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | Key rail |
| **8 224 15 063** | **Universal turning holder sq. 1" IC** | |
|  | Weight [kg]: | 3.100 |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 1" (25,4mm)<br>Sq. 1" (25,4mm) |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 100 |
| | Please note: | Key rail |
| **8 225 11 002** | **Cut-off holder sq. 20 R 1432** | |
| | Weight [kg]: | 1.120 |
| | Employment for: | left cutting tools |
| | Version: | Edge on side of turret |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 20 |
| | Coolant: | EXT |

© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts

| Part-# | Name | |
|---|---|---|
| **8 225 11 005** | **Cut-off holder sq. 20** | |
| | Weight [kg]: | 1.170 |
| | Employment for: | right cutting tools |
| | Version: | Edge on center of turret |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 20 |
| | Coolant: | EXT |
| **8 225 11 009** | **Cut-off holder sq. 3/4" R 1442** | |
| | Weight [kg]: | 1.110 |
| | Employment for: | left cutting tools |
| | Version: | Edge on side of turret |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 3/4" (19,05mm) |
| | Coolant: | EXT |
| **8 225 11 012** | **Cut-off holder sq. 3/4"** | |
| | Weight [kg]: | 1.200 |
| | Employment for: | right cutting tools |
| | Version: | Edge on center of turret |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 3/4" (19,05mm) |
| | Coolant: | EXT |
| **8 229 16 008** | **Tool holder C 4 IC** | |
| | Weight [kg]: | 3.430 |
| | Notation: | 180° reversible |
| | Version: | right |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | heimatec Capto(TM) C 4 |
| | Coolant: | IC |
| | Please note: | Check applicability; note tool length! |
| | Offset [mm]: | 55 |
| **8 229 16 009** | **Tool holder C 4 IC** | |
| | Weight [kg]: | 2.410 |
| | Notation: | 180° reversible |
| | Version: | right |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | heimatec Capto(TM) C 4 |
| | Coolant: | IC |
| | Please note: | Check applicability; note tool length! |
| | Offset [mm]: | 12 |
| **8 240 14 022** | **Boring bar holder Ø 10 - slotted** | |
|  | Weight [kg]: | 2.900 |
| | Notation: | 180° reversible |
| | Version: | slotted |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 10 |
| | Coolant: | EXT |


© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts

| Part-# | Name | |
|---|---|---|
| | Pressure max [bar]: | 100 |
| | Center distance [mm]: | 75 |
| **8 240 15 006** | **Collet chuck holder ER 25** | |
| | Weight [kg]: | 3.520 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | ER 25 |
| | Coolant: | IC/Ext |
| | Please note: | Insert reversible |
| | Center distance [mm]: | 75 |
| **8 240 15 007** | **Insert drill holder 16 IC** | |
| | Weight [kg]: | 4.540 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Tool adaption: | Whistle-Notch (DIN 1835 E) 16 |
| | Coolant: | IC |
| | Center distance [mm]: | 75 |
| **8 240 15 019** | **Collet chuck holder ER 25 AX UT IC** | |
| | Weight [kg]: | 3.380 |
| | Notation: | 180° reversible; offset |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | ER 25 A - u-tec |
| | Coolant: | IC/Ext |
| | Center distance [mm]: | 75 |
| **8 240 16 004** | **Tool holder HT 4 IC** | |
| | Weight [kg]: | 2.890 |
| | Notation: | 180° reversible; offset |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | HT 4 |
| | Coolant: | IC/Ext |
| | Center distance [mm]: | 75 |
| **8 240 16 008** | **Collet chuck holder ER 32** | |
| | Weight [kg]: | 3.200 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | ER 32 |
| | Coolant: | IC/Ext |
| | Please note: | Insert reversible |
| | Center distance [mm]: | 75 |
| **8 240 16 009** | **Insert drill holder 20 IC** | |
| | Weight [kg]: | 4.480 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Tool adaption: | Whistle-Notch (DIN 1835 E) 20 |
| | Coolant: | IC |
| | Center distance [mm]: | 75 |

*© heimatec GmbH • Subject to technical changes.*

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts

| Part-# | Name | |
|---|---|---|
| **8 240 16 030** | **Boring bar holder Ø 20** | |
| | Weight [kg]: | 3.940 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 20 |
| | Coolant: | IC/Ext |
| | Please note: | Housing rigid |
| | Center distance [mm]: | 75 |
| **8 240 16 034** | **Collet chuck holder ER 32** | |
| | Weight [kg]: | 3.060 |
| | Notation: | 180° reversible; offset |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | ER 32 |
| | Coolant: | IC/Ext |
| | Center distance [mm]: | 75 |
| **8 240 16 045** | **Tool holder C 4 IC** | |
|  | Weight [kg]: | 2.960 |
| | Notation: | 180° reversible |
| | Version: | offset; right |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | heimatec Capto(TM) C 4 |
| | Coolant: | IC |
| | Please note: | Check applicability; note tool length! |
| | Center distance [mm]: | 75 |
| **8 240 16 046** | **Tool holder C 4 IC** | |
| | Weight [kg]: | 3.480 |
| | Notation: | 180° reversible |
| | Version: | right |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | heimatec Capto(TM) C 4 |
| | Coolant: | IC |
| | Please note: | Check applicability; note tool length! |
| | Center distance [mm]: | 75 |
| **8 240 16 072** | **Tool holder C 4 IC** | |
|  | Weight [kg]: | 4.000 |
| | Notation: | 180° reversible |
| | Version: | right |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | heimatec Capto(TM) C 4 |
| | Coolant: | IC |
| | Please note: | Check applicability; note tool length! |
| | Center distance [mm]: | 95 |


© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts

| Part-# | Name | |
|---|---|---|
| **8 240 16 077** | **Boring bar holder Ø 20 - slotted** | |
|  | Weight [kg]: | 3.120 |
| | Notation: | 180° reversible |
| | Version: | slotted |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 20 |
| | Coolant: | EXT |
| | Pressure max [bar]: | 100 |
| | Center distance [mm]: | 75 |
| **8 240 17 005** | **Boring bar holder Ø 25** | |
|  | Weight [kg]: | 3.820 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 25 |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | Housing rigid |
| | Center distance [mm]: | 75 |
| **8 240 17 007** | **Boring bar holder Ø 25** | |
| | Weight [kg]: | 2.320 |
| | Notation: | 180° reversible |
| | Version: | offset |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 25 |
| | Coolant: | IC/Ext |
| | Please note: | Housing rigid |
| | Center distance [mm]: | 75 |
| **8 240 17 011** | **Boring bar holder Ø 25,4 (1")** | |
|  | Weight [kg]: | 3.800 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 1" (25,4mm) |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | Housing rigid |
| | Center distance [mm]: | 75 |
| **8 240 17 023** | **Insert drill holder 25 IC** | |
| | Weight [kg]: | 4.380 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Tool adaption: | Whistle-Notch (DIN 1835 E) 25 |
| | Coolant: | IC |
| | Center distance [mm]: | 75 |

© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts

| Part-# | Name | |
|---|---|---|
| **8 240 17 065** | **Boring bar holder Ø 25 - slotted** | |
| | Weight [kg]: | 3.670 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 25 |
| | Coolant: | EXT |
| | Please note: | Housing rigid |
| | Center distance [mm]: | 75 |
| **8 240 17 078** | **Boring bar holder Ø 1 1/4" - slotted** | |
| | Weight [kg]: | 3.440 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 1 1/4" (31,75mm) |
| | Coolant: | EXT |
| | Please note: | Housing rigid |
| | Center distance [mm]: | 75 |
| **8 240 18 010** | **Boring bar holder Ø 32** | |
|  | Weight [kg]: | 3.640 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 32 |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Please note: | Housing rigid |
| | Center distance [mm]: | 75 |
| **8 240 18 012** | **Boring bar holder Ø 32 offset** | |
| | Weight [kg]: | 2.420 |
| | Notation: | 180° reversible |
| | Version: | offset |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 32 |
| | Coolant: | IC/Ext |
| | Please note: | Housing rigid |
| | Center distance [mm]: | 75 |
| **8 240 18 016** | **Boring bar holder Ø 32** | |
| | Weight [kg]: | 4.370 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 32 |
| | Coolant: | IC/Ext |
| | Please note: | Housing rigid |
| | Center distance [mm]: | 90 |


© heimatec GmbH • Subject to technical changes.
heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts



| Part-# | Name | |
|---|---|---|
| **8 240 18 021** | **Insert drill holder 32 IC** | |
| | Weight [kg]: | 4.200 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Tool adaption: | Whistle-Notch (DIN 1835 E) 32 |
| | Coolant: | IC |
| | Center distance [mm]: | 75 |
| **8 240 18 033** | **Boring bar holder Ø 1 1/4"** | |
| | Weight [kg]: | 3.630 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 1 1/4" (31,75mm) |
| | Coolant: | IC/Ext |
| | Please note: | Housing rigid |
| | Center distance [mm]: | 75 |
| **8 240 18 037** | **Boring bar holder Ø 1 1/2"** | |
| | Weight [kg]: | 4.540 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 1 1/2" (38,1mm) |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Center distance [mm]: | 75 |
| **8 240 18 088** | **Boring bar holder Ø 32 offset** | |
| | Weight [kg]: | 4.200 |
| | Notation: | offset |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 32 |
| | Coolant: | IC/Ext |
| | Please note: | Front edge ø32- adapter 20mm from turret center offset |
| | Center distance [mm]: | 75 |
| **8 240 18 092** | **Boring bar holder Ø 32** | |
|  | Weight [kg]: | 5.250 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 32 |
| | Coolant: | IC/Ext |
| | Please note: | Check applicability! |
| | Center distance [mm]: | 110 |
| **8 240 18 098** | **Boring bar holder Ø 1 1/4"** | |
|  | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 1 1/4" (31,75mm) |
| | Coolant: | IC/Ext |
| | Please note: | Check applicability! |
| | Center distance [mm]: | 100 |

© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts

| Part-# | Name | |
|---|---|---|
| **8 240 19 009** | **Boring bar holder Ø 40** | |
|  | Weight [kg]: | 4.480 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 40 |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Center distance [mm]: | 75 |
| **8 240 19 025** | **Insert drill holder 40 IC** | |
|  | Weight [kg]: | 4.740 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Tool adaption: | Whistle-Notch (DIN 1835 E) 40 |
| | Coolant: | IC |
| | Center distance [mm]: | 75 |
| **8 240 19 139** | **Boring bar holder Ø 40** | |
| | Weight [kg]: | 4.760 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 40 |
| | Coolant: | IC |
| | Please note: | Check applicability! |
| | Center distance [mm]: | 100 |
| **8 240 19 142** | **Boring bar holder Ø 40 offset** | |
|  | Weight [kg]: | 5.000 |
| | Notation: | offset |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 40 |
| | Coolant: | IC/Ext |
| | Please note: | Front edge Ø40- adapter 60mm from turret center offset |
| | Center distance [mm]: | 75 |
| **8 240 19 143** | **Boring bar holder Ø 40 offset** | |
|  | Weight [kg]: | 4.000 |
| | Notation: | offset |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 40 |
| | Coolant: | IC/Ext |
| | Please note: | Front edge Ø40- adapter 20mm from turret center offset |
| | Center distance [mm]: | 75 |
| **8 244 12 025** | **Facing holder sq. 25** | |
|  | Weight [kg]: | 5.160 |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 25 |
| | Coolant: | EXT |
| | Please note: | Check applicability; note tool length! |


© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com


# JX-250 Ø65/75 Std. Revolver rechts

| Part-# | Name | |
|---|---|---|
| **8 249 15 001** | **Double collet chuck holder ER 25** | |
| | Weight [kg]: | 4.240 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | ER 25 |
| | Coolant: | IC/Ext |
| | Center distance [mm]: | 75 |
| **8 249 16 000** | **Double collet chuck holder ER 32** | |
| | Weight [kg]: | 4.000 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | ER 32 |
| | Coolant: | IC/Ext |
| | Center distance [mm]: | 75 |
| **8 249 16 009** | **Double tool holder HT 4** | |
| | Weight [kg]: | 3.660 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | HT 4 |
| | Coolant: | IC/Ext |
| | Center distance [mm]: | 75 |
| **8 249 16 015** | **Double tool holder C 4 IC** | |
|  | Weight [kg]: | 5.370 |
| | Notation: | 180° reversible |
| | Employment for: | Main- and sub spindle |
| | Version: | right |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | heimatec Capto(TM) C 4<br>heimatec Capto(TM) C 4 |
| | Coolant: | IC |
| | Please note: | Check applicability; note tool length! |
| | Center distance [mm]: | 75 |
| **8 249 16 027** | **Double tool holder C 4 IC** | |
|  | Weight [kg]: | 6.280 |
| | Notation: | 180° reversible |
| | Employment for: | Main- and sub spindle |
| | Version: | right |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | heimatec Capto(TM) C 4<br>heimatec Capto(TM) C 4 |
| | Coolant: | IC |
| | Please note: | Check applicability; note tool length! |
| | Center distance [mm]: | 95 |


© heimatec GmbH • Subject to technical changes.
heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts

| Part-# | Name | |
|---|---|---|
| **8 250 16 005** | **Multiple tool holder C 4 IC** | |
| | Weight [kg]: | 4.620 |
| | Employment for: | Main- and sub spindle |
| | Version: | right |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | heimatec Capto(TM) C 4 |
| | Coolant: | IC |
| | Please note: | Check applicability; note tool length! |
| | Offset [mm]: | ±55 |
| **8 251 11 000** | **Double turning holder sq. 20** | |
| | Weight [kg]: | 2.250 |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 20 |
| | Coolant: | EXT |
| **8 251 11 003** | **Double turning holder sq. 20** | |
|  | Weight [kg]: | 2.420 |
| | Notation: | 180° reversible |
| | Employment for: | right cutting tools |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 20 |
| | | Sq. 20 |
| | Coolant: | EXT |
| **8 251 11 007** | **Double turning holder sq. 3/4"** | |
| | Weight [kg]: | 2.390 |
| | Notation: | 180° reversible |
| | Employment for: | right cutting tools |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 3/4" (19,05mm) |
| | | Sq. 3/4" (19,05mm) |
| | Coolant: | EXT |
| **8 251 13 009** | **Combi multiple holder 6x sq. 3/4" IC** | |
| | Weight [kg]: | 6.780 |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 3/4" (19,05mm) |
| | | Sq. 3/4" (19,05mm) |
| | | Sq. 3/4" (19,05mm) |
| | | Sq. 3/4" (19,05mm) |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 100 |
| | Please note: | Key rail |
| **8 251 13 010** | **Combi multiple holder 3x sq. 3/4" IC** | |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 3/4" (19,05mm) |
| | | Sq. 3/4" (19,05mm) |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 100 |


© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts




| Part-# | Name | |
|---|---|---|
| | Please note: | Key rail |
| **8 251 14 064** | **Combi multiple holder 3x sq. 20 IC** | |
| | Weight [kg]: | 3.950 |
| | Employment for: | Main spindle |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 20 |
| | | Sq. 20 |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 100 |
| **8 251 14 066** | **Combi multiple holder 6x sq. 20 IC** | |
|  | Weight [kg]: | 6.780 |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 20 |
| | | Sq. 20 |
| | | Sq. 20 |
| | | Sq. 20 |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 100 |
| | Please note: | Key rail |
| **8 251 14 094** | **Combi multiple holder 3x sq. 20 IC** | |
| | Weight [kg]: | 3.820 |
| | Employment for: | Sub spindle |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 20 |
| | | Sq. 20 |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 100 |
| | Please note: | Key rail |
| **8 251 15 048** | **Combi double turning holder sq. 25 IC** | |
|  | Weight [kg]: | 5.000 |
| | Notation: | 180° reversible |
| | Employment for: | Main- and sub spindle |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 25 |
| | | Sq. 25 |
| | | Sq. 25 |
| | | Sq. 25 |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 100 |
| | Please note: | Key rail |
| **8 251 16 011** | **Multiple tool holder C 4 IC** | |
| | Weight [kg]: | 5.100 |
| | Employment for: | Sub spindle |
| | Version: | right |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | heimatec Capto(TM) C 4 |
| | | heimatec Capto(TM) C 4 - 15° |

© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com



# JX-250 Ø65/75 Std. Revolver rechts

| Part-# | Name | |
|---|---|---|
| | Coolant: | IC |
| | Please note: | Check applicability; note tool length! |
| | Offset [mm]: | 64 |
| | | 64 |
| **8 253 17 105** | **Multiple boring bar holder 2x Ø 25** | |
|  | Weight [kg]: | 5.560 |
| | Notation: | 180° reversible |
| | Employment for: | Main- and sub spindle |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 25 |
| | | Ø 25 - 15° |
| | Coolant: | IC/Ext |
| | Please note: | Check applicability! |
| | Center distance [mm]: | 75 |
| **8 253 17 125** | **Multiple boring bar holder Ø 25** | |
|  | Weight [kg]: | 3.720 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 25 |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Center distance [mm]: | 65/100 |
| **8 253 17 126** | **Multiple boring bar holder 3x Ø 25** | |
|  | Weight [kg]: | 6.560 |
| | Notation: | 180° reversible |
| | Employment for: | Main- and sub spindle |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 25 |
| | | Ø 25 |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 100 |
| | Center distance [mm]: | 65/100 |
| **8 253 17 127** | **Multiple boring bar holder Ø 1"** | |
|  | Weight [kg]: | 3.450 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Ø 1" (25,4mm) |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 140 |
| | Center distance [mm]: | 65/100 |
| **8 259 12 010** | **Multiple turning holder 2x sq. 20** | |
| | Weight [kg]: | 2.890 |
| | Notation: | 180° reversible |
| | Version: | Y-axes offset |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Sq. 20 |


© heimatec GmbH • Subject to technical changes.
heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com


# JX-250 Ø65/75 Std. Revolver rechts

| Part-# | Name | |
|---|---|---|
| | | Sq. 20 |
| | Coolant: | EXT |
| **8 263 19 002** | **Tool holder with rotating centering point** | |
|  | Weight [kg]: | 4.280 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Rotation max [1/min]: | 6000 |
| | Coolant: | EXT |
| | Please note: | Taper roller bearings |
| | Center distance [mm]: | 75 |
| **8 320 12 010** | **Cut-off holder, height adjustable SH 26 IC** | |
|  | Weight [kg]: | 1.680 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Clampshaft SH 26 |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 70 |
| **8 320 12 020** | **Cut-off holder, height adjustable SH 26 IC** | |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Clampshaft SH 26 |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 70 |
| | Please note: | with offset cut-off tool holder |
| **8 320 13 002** | **Cut-off holder, height adjustable SH 32 IC** | |
|  | Weight [kg]: | 1.570 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Clampshaft SH 32 |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 70 |
| **8 320 13 010** | **Cut-off holder, height adjustable SH 32 IC** | |
|  | Weight [kg]: | 1.730 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Clampshaft SH 32 |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 70 |
| | Please note: | Clampshaft internal |


© heimatec GmbH • Subject to technical changes.
heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

# JX-250 Ø65/75 Std. Revolver rechts

| Part-# | Name | |
|---|---|---|
| **8 320 13 015** | **Cut-off holder, height adjustable SH 32 IC** | |
|  | Weight [kg]: | 1.830 |
| | Notation: | 180° reversible |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Clampshaft SH 32 |
| | Coolant: | IC/Ext |
| | Pressure max [bar]: | 70 |
| | Please note: | with offset cut-off tool holder |
| **8 782 16 001** | **Spacer plate 20mm** | |
| | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Centering key slot b 20 |
| | Coolant: | EXT |
| | Please note: | Plate without fastening screws ! |
| **8 782 16 003** | **Spacer plate 25mm** | |
|  | Shank type: | BMT |
| | Machine adaption: | Centering key b 20 |
| | Tool adaption: | Centering key slot b 20 |
| | Coolant: | EXT |
| | Please note: | Plate without fastening screws ! |


© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen


T +49 7843 9466 0
info@heimatec.com
www.heimatec.com

11/2026

## heimatec.u-tec®

**heimatec.com**
Products / Tool change systems /
u-tec® Tool-changing system


versions see catalog



## heimatec.easy-quick

**heimatec.com**
Products / Tool change systems /
easy-quick HT quick-changing system


versions see catalog



## heimatec.Capto™

**heimatec.com**
Products / Tool change systems /
heimatec.Capto™ quick-changing system

versions see catalog



## heimatec.accessories

**heimatec.com**
Products / Accessories

versions see catalog



© heimatec GmbH • Subject to technical changes.

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
DE-77871 Renchen

T +49 7843 9466 0
info@heimatec.com
www.heimatec.com



11/2026




● heimatec overseas branches

○ global representations of heimatec

**heimatec GmbH**
Präzisionswerkzeuge
Carl-Benz-Str. 4
77871 Renchen
Germany

T +49 7843 9466 0
www.heimatec.com
info@heimatec.com

Please find the contact details of our worldwide trading partners on our website:
https://heimatec.com/business-partners

11/2026