

TOPSELLER -
many more available!

Live Tools


heimatec®

Doosan


Lynx 2100 LMSA/LMSB BMT 45

Part-#	Tool adaption	Rotation max [1/min]	Gear ratio	Coolant	Pressure max.	Center distance
Axial drilling and milling head						
8 010 45 129	ER 25 A - u-tec	10.000	1:1	EXT	--	--
8 010 45 220	ER 25 A - u-tec	15.000	1:1	IC/Ext	100 bar	--
Radial drilling and milling head						
8 030 45 594	ER 25 A - u-tec	12.000	1:1	EXT	--	65 mm
8 030 45 595	ER 25 A - u-tec	12.000	1:1	IC/Ext	140 bar	65 mm
Universal head, offset						
8 043 45 011	ER 25 A - u-tec	6.000	1:1	EXT	--	69 mm


Illustrations similar.




8 010 45 129



8 010 45 220



8 030 45 594



8 030 45 595

TOPSELLER -
many more available!

Static Tools

heimatec®

Doosan

Lynx 2100 LMSA/LMSB BMT 45

Part-#	Tool adaption	Coolant	Pressure max.	Center distance
--------	---------------	---------	---------------	-----------------

Universal turning holder

8 224 04 076 **Sq. 20** IC/Ext 140 bar --

Boring bar holder

8 240 07 039 **Ø 25** IC/Ext -- **65 mm**

8 240 07 018 **Ø 25** IC/Ext -- **85 mm**

8 240 08 003 **Ø 32** IC/Ext 80 bar **65 mm**

8 240 08 021 **Ø 32** IC/Ext 80 bar **85 mm**

8 240 09 014 **Ø 40** IC/Ext 80 bar **65 mm**

8 240 09 017 **Ø 40** IC/Ext -- **85 mm**

Combi facing holder

8 244 04 029 **Sq. 20** IC/Ext 100 bar --

Double boring bar holder

8 249 08 004 **Ø 32** IC/Ext -- **85 mm**

Combi multiple holder


8 251 04 046 **Sq. 3/4" (19,05mm)** EXT -- --

Cut-off holder, height adjustable

8 320 02 012 **Clampshaft SH 26** IC/Ext 70 bar --

8 320 03 011 **Clampshaft SH 32** IC/Ext 70 bar --


Illustrations similar.




8 224 04 076



8 240 07 039



8 244 04 029



8 251 04 046