

**TOPSELLER -**  
many more available!

Live Tools


**heimatec**®

# Doosan


## Lynx 220 LY/LSY

| Part-#                                                  | Tool adaption          | Rotation<br>max [1/min] | Gear ratio | Coolant | Pressure<br>max. | Center<br>distance |
|---------------------------------------------------------|------------------------|-------------------------|------------|---------|------------------|--------------------|
| <b>Axial drilling and milling head</b>                  |                        |                         |            |         |                  |                    |
| 8 010 45 129                                            | <b>ER 25 A - u-tec</b> | 10.000                  | 1:1        | EXT     | --               | --                 |
| 8 010 45 220                                            | <b>ER 25 A - u-tec</b> | 15.000                  | 1:1        | IC/Ext  | 100 bar          | --                 |
| <b>Radial drilling and milling head</b>                 |                        |                         |            |         |                  |                    |
| 8 030 45 594                                            | <b>ER 25 A - u-tec</b> | 12.000                  | 1:1        | EXT     | --               | <b>65 mm</b>       |
| 8 030 45 595                                            | <b>ER 25 A - u-tec</b> | 12.000                  | 1:1        | IC/Ext  | 140 bar          | <b>65 mm</b>       |
| <b>Radial drilling and milling head, double spindle</b> |                        |                         |            |         |                  |                    |
| 8 039 45 087                                            | <b>ER 25 A - u-tec</b> | 8.000                   | 1:1        | EXT     | --               | <b>80 mm</b>       |
| <b>Universal head, offset</b>                           |                        |                         |            |         |                  |                    |
| 8 043 45 011                                            | <b>ER 25 A - u-tec</b> | 6.000                   | 1:1        | EXT     | --               | <b>69 mm</b>       |


*Illustrations similar.*




8 010 45 129



8 010 45 220



8 030 45 594



8 030 45 595



8 039 45 087

**TOPSELLER -**  
many more available!

Static Tools


**heimatec**®

# Doosan

## Lynx 220 LY/LSY

| Part-#                                   | Tool adaption             | Coolant | Pressure max. | Center distance |
|------------------------------------------|---------------------------|---------|---------------|-----------------|
| <b>Universal turning holder</b>          |                           |         |               |                 |
| 8 224 05 011                             | <b>Sq. 25</b>             | EXT     | --            | --              |
| 8 224 05 030                             | <b>Sq. 25</b>             | IC/Ext  | 100 bar       | --              |
| <b>Boring bar holder</b>                 |                           |         |               |                 |
| 8 240 07 039                             | <b>Ø 25</b>               | IC/Ext  | --            | <b>65 mm</b>    |
| 8 240 08 003                             | <b>Ø 32</b>               | IC/Ext  | 80 bar        | <b>65 mm</b>    |
| 8 240 09 014                             | <b>Ø 40</b>               | IC/Ext  | 80 bar        | <b>65 mm</b>    |
| <b>Combi facing holder</b>               |                           |         |               |                 |
| 8 244 04 029                             | <b>Sq. 20</b>             | IC/Ext  | 100 bar       | --              |
| <b>Double turning holder</b>             |                           |         |               |                 |
| 8 251 04 008                             | <b>Sq. 20</b>             | EXT     | 80 bar        | --              |
| <b>Combi multiple holder</b>             |                           |         |               |                 |
| 8 251 04 045                             | <b>Sq. 20</b>             | EXT     | 80 bar        | --              |
| 8 251 04 046                             | <b>Sq. 3/4" (19,05mm)</b> | EXT     | --            | --              |
| <b>Cut-off holder, height adjustable</b> |                           |         |               |                 |
| 8 320 02 012                             | <b>Clampshaft SH 26</b>   | IC/Ext  | 70 bar        | --              |
| 8 320 03 011                             | <b>Clampshaft SH 32</b>   | IC/Ext  | 70 bar        | --              |


Illustrations similar.




8 224 05 030



8 240 07 039



8 244 04 029



8 251 04 046