

TOPSELLER -
many more available!

Live Tools


heimatec®

HAAS

ST-10/Y - BMT 45

Part-#	Tool adaption	Rotation max [1/min]	Gear ratio	Coolant	Pressure max.	Center distance
Radial drilling and milling head						
8 030 45 595	ER 25 A - u-tec	12.000	1:1	IC/Ext	140 bar	65 mm
Universal head, offset						
8 043 45 011	ER 25 A - u-tec	6.000	1:1	EXT	--	69 mm

Illustrations similar.



8 030 45 595

TOPSELLER -
many more available!

Static Tools


heimatec®

HAAS

ST-10/Y - BMT 45

Part-#	Tool adaption	Coolant	Pressure max.	Center distance
Universal turning holder				
8 224 04 003	Sq. 20	EXT	80 bar	--
8 224 04 060	Sq. 20	IC/Ext	100 bar	--
8 224 05 011	Sq. 25	EXT	--	--
8 224 05 030	Sq. 25	IC/Ext	100 bar	--
Boring bar holder				
8 240 07 039	Ø 25	IC/Ext	--	65 mm
8 240 08 003	Ø 32	IC/Ext	80 bar	65 mm
8 240 09 014	Ø 40	IC/Ext	80 bar	65 mm
Combi facing holder				
8 244 04 029	Sq. 20	IC/Ext	100 bar	--
Multiple turning holder				
8 259 01 015	Sq. 20	EXT	--	--
Cut-off holder, height adjustable				
8 320 02 012	Clampshaft SH 26	IC/Ext	70 bar	--
8 320 03 011	Clampshaft SH 32	IC/Ext	70 bar	--


Illustrations similar.




8 224 04 060



8 240 07 039



8 244 04 029



8 259 01 015