

TOPSELLER -
many more available!

Live Tools

heimatec®

HAAS

ST-10/Y Hybrid VB 12

Part-#	Tool adaption	Rotation max [1/min]	Gear ratio	Coolant	Pressure max.	Center distance
Axial drilling and milling head						
8 010 46 188	ER 32 A - u-tec	6.000	1:1	EXT	--	--
8 010 46 215	ER 32 A - u-tec	6.000	1:1	IC/Ext	100 bar	--
Radial drilling and milling head						
8 030 46 321	ER 32 A - u-tec	6.000	1:1	EXT	--	69 mm
8 030 46 330	ER 32 A - u-tec	6.000	1:1	IC/Ext	140 bar	69 mm
Universal head						
8 040 45 040	ER 25 A - u-tec	6.000	1:1	EXT	--	87 mm


Illustrations similar.




8 010 46 188




8 010 46 215



8 030 46 321



8 030 46 330



8 040 45 040

TOPSELLER -
many more available!

Static Tools

heimatec®

HAAS

ST-10/Y Hybrid VB 12

Part-#	Tool adaption	Coolant	Pressure max.
Tool holder			
8 210 45 002	ER 25	IC	--
8 210 46 000	ER 32	IC	--
8 210 47 001	Ø 25	IC/Ext	--
8 210 49 005	Ø 50	IC/Ext	--
Boring bar holder			
8 219 47 004	Ø 25	IC/Ext	--
8 219 48 006	Ø 32	IC/Ext	--
Cut-off holder, height adjustable			
8 320 43 009	Clampshaft SH 32	IC/Ext	70 bar

Illustrations similar.



8 210 45 002



8 210 46 000



8 219 47 004



8 219 48 006



8 320 43 009