

**TOPSELLER -**  
many more available!

Live Tools

**heimatec**®

# SMEC

## SL 2000 M

| Part-#                                         | Tool adaption              | Rotation<br>max [1/min] | Gear ratio | Coolant | Pressure<br>max. | Center<br>distance |
|------------------------------------------------|----------------------------|-------------------------|------------|---------|------------------|--------------------|
| <b>Axial drilling and milling head</b>         |                            |                         |            |         |                  |                    |
| 8 010 55 039                                   | <b>ER 25 A - u-tec</b>     | 12.000                  | 1:1        | EXT     | 140 bar          | --                 |
| 8 010 55 057                                   | <b>ER 25 A - u-tec</b>     | 12.000                  | 1:1        | IC/Ext  | 100 bar          | --                 |
| 8 010 56 039                                   | <b>ER 32 A - u-tec</b>     | 12.000                  | 1:1        | EXT     | 140 bar          | --                 |
| 8 010 56 089                                   | <b>ER 32 A - u-tec</b>     | 12.000                  | 1:1        | IC/Ext  | 100 bar          | --                 |
| 8 010 56 118                                   | <b>heimatec Capto™ C 4</b> | 6.000                   | 1:1        | EXT     | --               | --                 |
| 8 010 56 119                                   | <b>heimatec Capto™ C 4</b> | 6.000                   | 1:1        | IC/Ext  | 100 bar          | --                 |
| <b>Axial drilling and milling head, offset</b> |                            |                         |            |         |                  |                    |
| 8 019 55 054                                   | <b>ER 25 A - u-tec</b>     | 6.000                   | 1:1        | IC/Ext  | 140 bar          | --                 |
| <b>Radial drilling and milling head</b>        |                            |                         |            |         |                  |                    |
| 8 030 55 175                                   | <b>ER 25 A - u-tec</b>     | 12.000                  | 1:1        | EXT     | --               | <b>60 mm</b>       |
| 8 030 55 176                                   | <b>ER 25 A - u-tec</b>     | 12.000                  | 1:1        | IC/Ext  | 140 bar          | <b>60 mm</b>       |
| <b>Universal head, offset</b>                  |                            |                         |            |         |                  |                    |
| 8 043 54 006                                   | <b>ER 16 A - u-tec</b>     | 6.000                   | 1:1        | EXT     | --               | <b>50 mm</b>       |
| 8 043 55 005                                   | <b>ER 25 A - u-tec</b>     | 6.000                   | 1:1        | EXT     | --               | <b>50 mm</b>       |


*Illustrations similar.*



8 010 55 039




8 010 55 057



8 019 55 054



8 030 55 175



8 043 54 006

**TOPSELLER -**  
many more available!

Static Tools


**heimatec**®

# SMEC


## SL 2000 M

| Part-#                                   | Tool adaption           | Coolant | Pressure max. |
|------------------------------------------|-------------------------|---------|---------------|
| <b>Cut-off holder</b>                    |                         |         |               |
| 8 224 03 003                             | <b>Clampshaft SH 32</b> | EXT     | --            |
| <b>Universal turning holder</b>          |                         |         |               |
| 8 224 04 062                             | <b>Sq. 20</b>           | IC/Ext  | 100 bar       |
| 8 224 05 029                             | <b>Sq. 25</b>           | IC/Ext  | 140 bar       |
| <b>Combi facing holder</b>               |                         |         |               |
| 8 244 05 003                             | <b>Sq. 25</b>           | EXT     | 80 bar        |
| <b>Cut-off holder, height adjustable</b> |                         |         |               |
| 8 320 03 008                             | <b>Clampshaft SH 32</b> | IC/Ext  | 140 bar       |


*Illustrations similar.*




8 224 03 003




8 224 04 062



8 224 05 029



8 244 05 003



8 320 03 008