

Nakamura
STS-40



High-tech from heimatec - heimatec - Tools and systems for productive turning and milling

heimatec belongs to the international technology and quality leaders for precision tools and specializes in the development and production of high-precision static and live tools for all CNC lathes, CNC turn-/mill machines and CNC machining centers.

The range of products* spans from static BMT and VDI tool holders, live tools up to highly complex customer-specific individual solutions. heimatec, headquartered in Renchen, has a own subsidiary in Asia and India and numerous representatives as well as trading partners all over the world.

*OUR PRODCUTS

Static tool holders

Live tool units

Precision tools

Tools for turning and machining centres

Tools for swiss type lathes

Tool changing and uick-change systems



Tool systems for gear production

Digital tool management

This catalogue, including all its parts, is protected by copyright. Any use outside the restricted limitations of the Copyright Act without the consent of heimatec is inadmissible and liable to prosecution. This applies in particular to duplication, translation, microfilming and storage and processing in electronic systems.

heimatec GmbH reserves the right to make technical changes at any time without giving prior notice. This applies in particular to adjustments at any time to meet new or changed international standards, or in case of further developments of our products or manufacturing processes.

The current version of our General Terms and Conditions can be found on our website.

Part-#	Name	
8 010 66 058	Axial drilling and milling head ER 32 AX UT	
	Weight [kg]:	5.320
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	80
	Rotation max [1/min]:	4000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	Combi bearing
8 010 66 059	Axial drilling and milling head ER 32 AX UT IC	
	Weight [kg]:	5.650
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	80
	Rotation max [1/min]:	4000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	25
	Please note:	Combi bearing
8 010 66 060	Axial drilling and milling head ER 32 AX UT IC	
	Weight [kg]:	5.680
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	80
	Rotation max [1/min]:	4000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	80
	Please note:	Combi bearing; dryrun possible
8 010 67 030	Axial drilling and milling head ER 40 AX UT IC	
	Weight [kg]:	5.580
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	ER 40 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	80
	Rotation max [1/min]:	4000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	80
	Please note:	Combi bearing; dryrun possible

Part-#	Name	
8 010 67 079	Axial drilling and milling head ER 40 AX UT	
	Weight [kg]:	5.320
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	ER 40 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	80
	Rotation max [1/min]:	4000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	Combi bearing
8 010 67 080	Axial drilling and milling head ER 40 AX UT IC	
	Weight [kg]:	5.650
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	ER 40 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	80
	Rotation max [1/min]:	4000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	25
	Please note:	Combi bearing
8 010 68 005	Axial drilling and milling head HT 6 IC	
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	HT 6
	Gear ratio [i]:	1:1
	Torque max [Nm]:	80
	Rotation max [1/min]:	4000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	25
	Please note:	Combi bearing
8 010 68 006	Axial drilling and milling head HT 6	
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	HT 6
	Gear ratio [i]:	1:1
	Torque max [Nm]:	80
	Rotation max [1/min]:	4000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	Combi bearing

Part-#	Name	
8 010 68 016	Axial drilling and milling head HT 6 IC	
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	HT 6
	Gear ratio [i]:	1:1
	Torque max [Nm]:	80
	Rotation max [1/min]:	4000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	70
	Please note:	Combi bearing
8 011 65 022	Axial milling head universal arbor 22	
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	Universal arbor 22
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	4000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	Combi bearing
8 011 65 024	Axial milling head universal arbor 22 IC	
	Weight [kg]:	6.990
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	Universal arbor 22
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	4000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	25
	Please note:	Combi bearing
8 011 66 012	Axial milling head universal arbor 27 IC	
	Weight [kg]:	7.090
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	Universal arbor 27
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	4000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	25
	Please note:	Combi bearing

Part-#	Name	
8 011 67 007	Axial milling head universal arbor 32 IC	
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	Universal arbor 32
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	4000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	25
	Please note:	Combi bearing
8 019 66 018	Axial drilling and milling head ER 32 AX UT	
	Weight [kg]:	10.450
	Notation:	offset; 180° reversible
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	63
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	stronger bearing
	Offset [mm]:	60
8 019 66 023	Axial drilling and milling head ER 32 AX UT IC	
	Notation:	offset; 180° reversible
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	1:3
	Torque max [Nm]:	25
	Rotation max [1/min]:	12000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Please note:	stronger bearing
	Offset [mm]:	60
8 019 67 012	Axial drilling and milling head ER 40 AX UT IC	
	Notation:	offset; 180° reversible
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	ER 40 A - u-tec
	Gear ratio [i]:	2:1
	Torque max [Nm]:	100
	Rotation max [1/min]:	3000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Please note:	stronger bearing
	Offset [mm]:	60

Part-#	Name
--------	------

8 030 66 040



Angle-mill- and drill holder ER 32 AX UT IC

Weight [kg]:	12.800
Notation:	180° reversible
Tool drive:	Flat (~DIN 1809)
Shank size [mm]:	75.00
Shank type:	BMT
Tool adaption:	ER 32 A - u-tec
Gear ratio [i]:	1:1
Torque max [Nm]:	50
Rotation max [1/min]:	5000
Rotating direction:	opposite
Coolant:	IC/Ext
Pressure max [bar]:	140
Please note:	Combi bearing
Center distance [mm]:	90

8 030 66 071

Radial drilling and milling head ER 32 AX UT

Weight [kg]:	11.730
Notation:	180° reversible
Tool drive:	Flat (~DIN 1809)
Shank size [mm]:	75.00
Shank type:	BMT
Tool adaption:	ER 32 A - u-tec
Gear ratio [i]:	1:1
Torque max [Nm]:	50
Rotation max [1/min]:	5000
Rotating direction:	opposite
Coolant:	EXT
Please note:	Combi bearing
Center distance [mm]:	90

8 030 66 262



Radial drilling and milling head ER 32 AX UT IC


Weight [kg]:	8.540
Notation:	180° reversible
Tool drive:	Flat (~DIN 1809)
Shank size [mm]:	75.00
Shank type:	BMT
Tool adaption:	ER 32 A - u-tec
Gear ratio [i]:	1:1
Torque max [Nm]:	50
Rotation max [1/min]:	6000
Rotating direction:	opposite
Coolant:	IC/Ext
Pressure max [bar]:	140
Center distance [mm]:	90

8 030 67 036

Radial drilling and milling head ER 40 AX UT IC

Weight [kg]:	12.740
Notation:	180° reversible
Tool drive:	Flat (~DIN 1809)
Shank size [mm]:	75.00
Shank type:	BMT
Tool adaption:	ER 40 A - u-tec
Gear ratio [i]:	1:1
Torque max [Nm]:	50
Rotation max [1/min]:	5000
Rotating direction:	opposite



Part-#	Name	
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Please note:	Combi bearing
	Center distance [mm]:	90
8 030 68 001	Radial drilling and milling head HT 6	
	Notation:	180° reversible
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	HT 6
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	stronger bearing
	Center distance [mm]:	90
8 030 68 002	Radial drilling and milling head HT 6 IC	
	Weight [kg]:	13.070
	Notation:	180° reversible
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	HT 6
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Please note:	stronger bearing
	Center distance [mm]:	90
8 031 65 003	Radial milling head universal arbor 22	
	Notation:	180° reversible
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	Universal arbor 22
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	5000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	Combi bearing
	Center distance [mm]:	90
8 031 66 000	Radial milling head universal arbor 27	
	Notation:	180° reversible
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	Universal arbor 27
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	5000

Part-#	Name	
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	Combi bearing
	Center distance [mm]:	90
8 039 65 003	Radial drilling and milling head Weldon 16	
	Weight [kg]:	15.960
	Notation:	45° angle
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	Weldon (DIN 1835 b) 16
	Gear ratio [i]:	1:1
	Torque max [Nm]:	40
	Rotation max [1/min]:	4000
	Rotating direction:	same
	Coolant:	EXT
8 039 65 004	Radial drilling and milling head Weldon 16 IC	
	Weight [kg]:	15.960
	Notation:	45° angle
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	Weldon (DIN 1835 b) 16
	Gear ratio [i]:	1:1
	Torque max [Nm]:	40
	Rotation max [1/min]:	4000
	Rotating direction:	same
	Coolant:	IC/Ext
8 039 65 006	Radial drilling and milling head ER 25	
	Weight [kg]:	27.800
	Notation:	7,125° angle
	Employment for:	Inside operation
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	ER 25
	Gear ratio [i]:	1:1
	Torque max [Nm]:	20
	Rotation max [1/min]:	4000
	Rotating direction:	same
	Coolant:	EXT
8 039 66 012	Radial drilling and milling head ER 32 AX UT	
	Notation:	180° reversible
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same/opposite
	Coolant:	EXT
	Please note:	stronger bearing

Part-#	Name	
	Center distance [mm]:	90
8 040 65 009	Universal head ± 90° adjustable ER 25 AX UT	
	Weight [kg]:	7.000
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	ER 25 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	stronger bearing
	Center distance [mm]:	80,5
8 040 65 014	Universal head ± 90° adjustable ER 25 AX UT IC	
	Weight [kg]:	6.820
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	75.00
	Shank type:	BMT
	Tool adaption:	ER 25 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Please note:	stronger bearing
	Center distance [mm]:	80,5
8 202 20 019	Basic holder longitudinal seat FN 12	
	Weight [kg]:	2.050
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key b 30
	Tool adaption:	Interface FN 12
	Coolant:	EXT
	Center distance [mm]:	20
8 224 22 000	Cut-off holder sq. 25 - Z 3431	
	Weight [kg]:	2.380
	Employment for:	right cutting tools
	Version:	Edge on side of turret
	Shank type:	BMT
	Machine adaption:	Centering key b 30
	Tool adaption:	Sq. 25
	Coolant:	EXT
8 224 23 000	Cut-off holder SH 32 - Z 3431-2	
	Weight [kg]:	2.300
	Shank type:	BMT
	Machine adaption:	Centering key b 30
	Tool adaption:	Clampshaft SH 32
	Coolant:	IC/Ext

Part-#	Name	
8 224 25 012	Universal turning holder sq. 25	
	Weight [kg]:	4.680
	Shank type:	BMT
	Machine adaption:	Centering key b 30
	Tool adaption:	Sq. 25
		Sq. 25
	Coolant:	EXT
8 225 22 000	Cut-off holder sq. 25	
	Weight [kg]:	2.400
	Employment for:	left cutting tools
	Version:	Edge on side of turret
	Shank type:	BMT
	Machine adaption:	Centering key b 30
	Tool adaption:	Sq. 25
	Coolant:	EXT
8 240 28 001	Boring bar holder Ø 32	
	Weight [kg]:	8.380
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key slot b 30
	Tool adaption:	Ø 32
	Coolant:	IC/Ext
	Center distance [mm]:	105
8 240 28 002	Boring bar holder Ø 32	
	Weight [kg]:	11.740
	Notation:	offset; 180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key slot b 30
	Tool adaption:	Ø 32
	Coolant:	IC/Ext
	Center distance [mm]:	105
8 240 29 003	Boring bar holder Ø 50 - R 3437 similar to	
	Weight [kg]:	11.600
	Notation:	offset
	Shank type:	BMT
	Machine adaption:	Centering key slot b 30
	Tool adaption:	Ø 50
	Coolant:	IC/Ext
	Center distance [mm]:	105
	Offset [mm]:	25
8 240 29 004	Boring bar holder Ø 40 - R 3417	
	Weight [kg]:	8.060
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key slot b 30
	Tool adaption:	Ø 40
	Coolant:	IC/Ext
	Center distance [mm]:	105

Part-#	Name	
8 240 29 006	Boring bar holder Ø 50 - R 3437	
	Weight [kg]:	9.340
	Shank type:	BMT
	Machine adaption:	Centering key slot b 30
	Tool adaption:	Ø 50
	Coolant:	IC/Ext
	Center distance [mm]:	105
8 240 29 028	Boring bar holder Ø 2"	
	Weight [kg]:	9.290
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key slot b 30
	Tool adaption:	Ø 2" (50,8mm)
	Coolant:	IC/Ext
	Center distance [mm]:	105
8 240 29 030	Boring bar holder Ø 40	
	Weight [kg]:	10.420
	Notation:	offset; 180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key slot b 30
	Tool adaption:	Ø 40
	Coolant:	IC/Ext
	Center distance [mm]:	105
8 244 22 000	Facing holder sq.25	
	Weight [kg]:	5.590
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key slot b 30
	Tool adaption:	Sq. 25
	Coolant:	EXT
8 244 22 001	Facing holder sq.25	
	Weight [kg]:	5.580
	Version:	special
	Shank type:	BMT
	Machine adaption:	Centering key slot b 30
	Tool adaption:	Sq. 25
	Coolant:	EXT
	Please note:	with 2. coolant nozzle
8 251 22 001	Double turning holder sq. 25	
	Weight [kg]:	5.260
	Shank type:	BMT
	Machine adaption:	Centering key b 30
	Tool adaption:	Sq. 25
		Sq. 25
	Coolant:	EXT

Part-#	Name	
8 253 28 000	Double boring bar holder Ø 32	
	Weight [kg]:	8.420
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key b 30
	Tool adaption:	Ø 32
	Coolant:	IC/Ext
	Center distance [mm]:	70/122,5
8 253 29 000	Multiple boring bar holder Ø 40	
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key b 30
	Tool adaption:	Ø 40
	Coolant:	IC/Ext
	Center distance [mm]:	70/122,5
8 320 29 023	Cut-off holder, height adjustable 845 IC	
	Weight [kg]:	2.590
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key b 30
	Tool adaption:	 System 845
	Coolant:	IC
	Pressure max [bar]:	70
8 320 29 024	Cut-off holder, height adjustable 845 IC	
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key b 30
	Tool adaption:	 System 845
	Coolant:	IC
	Pressure max [bar]:	70
	Please note:	Clampshaft internal



heimatec.u-tec®

heimatec.com

Products / Tool change systems /
u-tec® Tool-changing system



versions see catalog



heimatec.easy-quick

heimatec.com

Products / Tool change systems /
easy-quick HT quick-changing system



versions see catalog



heimatec.Capto™

heimatec.com

Products / Tool change systems /
heimatec.Capto™ quick-changing system



versions see catalog



heimatec.accessories

heimatec.com

Products / Accessories



versions see catalog





● heimatec overseas branches

○ global representations of heimatec

heimatec[®]

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
77871 Renchen
Germany

T +49 7843 9466 0
www.heimatec.com
info@heimatec.com

Please find the contact details of our worldwide trading partners on our website:
<https://heimatec.com/business-partners>