

SPINNER
TD 42



High-tech from heimatec - heimatec - Tools and systems for productive turning and milling

heimatec belongs to the international technology and quality leaders for precision tools and specializes in the development and production of high-precision static and live tools for all CNC lathes, CNC turn-/mill machines and CNC machining centers.

The range of products* spans from static BMT and VDI tool holders, live tools up to highly complex customer-specific individual solutions. heimatec, headquartered in Renchen, has a own subsidiary in Asia and India and numerous representatives as well as trading partners all over the world.

*OUR PRODCUTS

Static tool holders

Live tool units

Precision tools

Tools for turning and machining centres

Tools for swiss type lathes

Tool changing and uick-change systems



Tool systems for gear production

Digital tool management



This catalogue, including all its parts, is protected by copyright. Any use outside the restricted limitations of the Copyright Act without the consent of heimatec is inadmissible and liable to prosecution. This applies in particular to duplication, translation, microfilming and storage and processing in electronic systems.

heimatec GmbH reserves the right to make technical changes at any time without giving prior notice. This applies in particular to adjustments at any time to meet new or changed international standards, or in case of further developments of our products or manufacturing processes.

The current version of our General Terms and Conditions can be found on our website.


Part-#	Name	
8 010 25 098	Axial drilling and milling head ER 25 AX UT	
	Weight [kg]:	2.360
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	ER 25 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	8000
	Rotating direction:	same
	Coolant:	EXT
8 010 25 099	Axial drilling and milling head ER 25 AX UT IC	
	Weight [kg]:	2.560
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	ER 25 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	8000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	25
8 010 26 037	Axial drilling and milling head HT 4	
	Weight [kg]:	2.580
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	HT 4
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	8000
	Rotating direction:	same
	Coolant:	EXT
8 010 26 038	Axial drilling and milling head HT 4 IC	
	Weight [kg]:	2.560
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	HT 4
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	8000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	25
8 011 24 015	Axial milling head universal arbor 16	
	Weight [kg]:	2.460
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	Universal arbor 16
	Gear ratio [i]:	1:1

Part-#	Name	
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	Taper roller bearings
8 011 25 013	Axial milling head universal arbor 22	
	Weight [kg]:	2.580
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	Universal arbor 22
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	8000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	Taper roller bearings
8 016 24 000	Axial drilling and milling head HT 2	
	Notation:	offset; 180° reversible
	Version:	doubletoothed
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	HT 2
	Gear ratio [i]:	1:2
	Torque max [Nm]:	16
	Rotation max [1/min]:	16000
	Rotating direction:	opposite
	Coolant:	EXT
	Offset [mm]:	34,5
8 016 24 005	Axial drilling and milling head ER 16 AX UT	
	Weight [kg]:	3.700
	Notation:	offset; 180° reversible
	Version:	doubletoothed
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	ER 16 A - u-tec
	Gear ratio [i]:	1:2
	Torque max [Nm]:	16
	Rotation max [1/min]:	16000
	Rotating direction:	opposite
	Coolant:	EXT
8 036 24 016	Radial drilling and milling head ER 16 AX UT	
	Version:	doubletoothed
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	ER 16 A - u-tec
	Gear ratio [i]:	1:2
	Torque max [Nm]:	8
	Rotation max [1/min]:	16000
	Rotating direction:	opposite
	Coolant:	EXT

Part-#	Name	
	Center distance [mm]:	75
8 036 24 020	Radial milling head universal arbor 16	
	Weight [kg]:	3.630
	Version:	Special; doubletoothed
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	Universal arbor 16
	Gear ratio [i]:	1:1
	Torque max [Nm]:	16
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	stronger bearing
	Center distance [mm]:	75
8 036 25 010	Radial drilling and milling head ER 25	
	Weight [kg]:	3.200
	Version:	doubletoothed
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	ER 25
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	8000
	Rotating direction:	opposite
	Coolant:	EXT
	Center distance [mm]:	75
8 036 25 011	Radial drilling and milling head ER 25 IC	
	Weight [kg]:	3.600
	Version:	doubletoothed
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	ER 25
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	8000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Center distance [mm]:	75
8 036 25 025	Radial drilling and milling head ER 25 AX UT	
	Weight [kg]:	3.410
	Version:	doubletoothed
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	ER 25 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	8000
	Rotating direction:	opposite

SPINNER


TD 42

Part-#	Name	
	Coolant:	EXT
	Center distance [mm]:	75
8 036 25 026	Radial drilling and milling head ER 25	
	Weight [kg]:	4.000
	Version:	doubletoothed; special
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	ER 25
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	8000
	Rotating direction:	opposite
	Coolant:	EXT
	Center distance [mm]:	100
8 036 25 047	Radial drilling and milling head ER 25 IC	
	Version:	doubletoothed
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	ER 25
	Gear ratio [i]:	1:2
	Torque max [Nm]:	16
	Rotation max [1/min]:	12000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Center distance [mm]:	75
8 036 26 033	Radial drilling and milling head HT 4	
	Weight [kg]:	3.230
	Version:	doubletoothed
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	HT 4
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	Fixation slide stone
	Center distance [mm]:	75
8 039 25 024	Radial drilling and milling head ER 25	
	Weight [kg]:	3.700
	Employment for:	Main- and sub spindle
	Version:	doubletoothed; double spindle
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	ER 25
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	8000

Part-#	Name	
	Rotating direction:	same/opposite
	Coolant:	EXT
	Please note:	stronger bearing
	Center distance [mm]:	75
8 039 25 046	Radial drilling and milling head ER 25	
	Weight [kg]:	4.520
	Employment for:	Main- and sub spindle
	Version:	doubletoothed; double spindle; special
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	ER 25
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	8000
	Rotating direction:	same/opposite
	Coolant:	EXT
	Please note:	stronger bearing
	Center distance [mm]:	100
8 040 24 042	Universal head ± 90° adjustable ER 16	
	Version:	right
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	ER 16
	Gear ratio [i]:	1:1
	Torque max [Nm]:	10
	Rotation max [1/min]:	8000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	note useable swivel range!
	Center distance [mm]:	65
8 040 24 065	Universal head ± 90° adjustable ER 16 AX UT IC	
	Weight [kg]:	4.290
	Version:	left
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	ER 16 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Center distance [mm]:	85
8 040 24 068	Universal head ± 90° adjustable ER 16 AX UT	
	Weight [kg]:	4.290
	Version:	right
	Tool drive:	Flat (~DIN 1809)
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	ER 16 A - u-tec
	Gear ratio [i]:	1:1


SPINNER

TD 42

Part-#	Name	
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Center distance [mm]:	85
8 216 22 000	Tool holder C1/C4-25x20/16	
	Weight [kg]:	1.150
	Employment for:	VDI 25
	Version:	doubletoothed
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	Sq. 20/16
	Coolant:	EXT
8 230 25 008	Collet chuck holder ER 25	
	Version:	right
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	ER 25
	Coolant:	IC/Ext
	Please note:	demountable in left version
	Center distance [mm]:	75
8 230 26 016	Collet chuck holder ER 32	
	Weight [kg]:	2.740
	Version:	right, offset
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	ER 32
	Coolant:	IC/Ext
	Center distance [mm]:	75
8 230 27 024	Boring bar holder Ø 25	
	Weight [kg]:	2.860
	Version:	right
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	Ø 25
	Coolant:	IC/Ext
	Please note:	demountable in left version
	Center distance [mm]:	75
8 230 27 041	Boring bar holder Ø 30	
	Weight [kg]:	2.770
	Version:	right
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	Ø 30
	Coolant:	IC/Ext
	Please note:	demountable in left version
	Center distance [mm]:	75

SPINNER

TD 42

Part-#	Name	
	8 230 27 049 Boring bar holder Ø 25	Weight [kg]: 3.420 Version: right Shank size [mm]: 25.00 Shank type: VDI Tool adaption: Ø 25 Coolant: IC/Ext Please note: demountable in left version Center distance [mm]: 95
	8 230 27 054 Boring bar holder Ø 1"	Weight [kg]: 2.850 Version: right Shank size [mm]: 25.00 Shank type: VDI Tool adaption: Ø 1" (25,4mm) Coolant: IC/Ext Please note: demountable in left version Center distance [mm]: 75
	8 230 28 019 Boring bar holder Ø 32	Notation: offset Version: right Shank size [mm]: 25.00 Shank type: VDI Tool adaption: Ø 32 Coolant: IC/Ext Center distance [mm]: 75
	8 231 28 003 Boring bar holder Ø 32	Notation: offset Version: left Shank size [mm]: 25.00 Shank type: VDI Tool adaption: Ø 32 Coolant: IC/Ext Center distance [mm]: 75
	8 236 26 006 Tool holder HT 4	Notation: 180° reversible Version: doubletoothed Shank size [mm]: 25.00 Shank type: VDI Tool adaption: HT 4 Coolant: IC/Ext Please note: Fixation slide stone Center distance [mm]: 75
	8 236 27 014 Boring bar holder Ø 25	Version: doubletoothed Shank size [mm]: 25.00 Shank type: VDI Tool adaption: Ø 25 Coolant: IC/Ext Pressure max [bar]: 100 Center distance [mm]: 95

Part-#	Name	
8 239 26 029	Double tool holder HT 4	
	Weight [kg]:	2.840
	Employment for:	Main- and sub spindle
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	HT 4
	Coolant:	IC/Ext
	Center distance [mm]:	75
8 251 23 003	Combi double turning holder sq.20/16	
	Weight [kg]:	1.920
	Employment for:	Main- and sub spindle
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	Sq. 20/16
	Coolant:	EXT
	Please note:	usable as C1, C2, C3, C4
8 253 25 001	Double boring bar holder Ø 16	
	Weight [kg]:	4.900
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	Ø 16
	Coolant:	IC/Ext
	Center distance [mm]:	70/105
8 253 26 010	Multiple tool holder HT 4	
	Weight [kg]:	4.580
	Version:	Special; double spindle
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	HT 4 HT 4 HT 4 HT 4
	Coolant:	IC/Ext
	Please note:	Check applicability; tool height 132,5 mm
	Center distance [mm]:	70/112
8 253 26 011	Double tool holder HT 4	
	Weight [kg]:	4.550
	Version:	Special
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	HT 4 HT 4
	Coolant:	IC/Ext
	Please note:	Check applicability; tool height 132,5 mm
	Center distance [mm]:	70/112
8 253 27 008	Double boring bar holder Ø 25	
	Weight [kg]:	4.430
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	Ø 25
	Coolant:	IC/Ext
	Center distance [mm]:	70/105

SPINNER TD 42

Part-#	Name	
8 262 29 006	Stock stop VDI 25 - Ø 60 OD turret	
	Weight [kg]:	2.740
	Notation:	rotating
	Version:	left
	Shank size [mm]:	25.00
	Shank type:	VDI
	Rotation max [1/min]:	8000
	Coolant:	no
	Please note:	Lenght adjustable
	Center distance [mm]:	75
8 320 23 014	Cut-off holder, height adjustable SH 32 IC	
	Weight [kg]:	1.370
	Version:	universal
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	Clampshaft SH 32
	Coolant:	IC/Ext
	Pressure max [bar]:	70
8 320 23 020	Cut-off holder, height adjustable SH 32 IC	
	Weight [kg]:	1.540
	Version:	universal
	Shank size [mm]:	25.00
	Shank type:	VDI
	Tool adaption:	Clampshaft SH 32
	Coolant:	IC/Ext
	Pressure max [bar]:	70
	Please note:	Clampshaft internal



● heimatec overseas branches

○ global representations of heimatec

heimatec[®]

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
77871 Renchen
Germany

T +49 7843 9466 0
www.heimatec.com
info@heimatec.com

Please find the contact details of our worldwide trading partners on our website:
<https://heimatec.com/business-partners>