

HAAS
ST-30SS/SSY -
Hybrid VB 24



High-tech from heimatec - heimatec - Tools and systems for productive turning and milling

heimatec belongs to the international technology and quality leaders for precision tools and specializes in the development and production of high-precision static and live tools for all CNC lathes, CNC turn-/mill machines and CNC machining centers.

The range of products* spans from static BMT and VDI tool holders, live tools up to highly complex customer-specific individual solutions. heimatec, headquartered in Renchen, has a own subsidiary in Asia and India and numerous representatives as well as trading partners all over the world.

*OUR PRODCUTS

Static tool holders

Live tool units

Precision tools

Tools for turning and machining centres

Tools for swiss type lathes

Tool changing and uick-change systems


Tool systems for gear production

Digital tool management


This catalogue, including all its parts, is protected by copyright. Any use outside the restricted limitations of the Copyright Act without the consent of heimatec is inadmissible and liable to prosecution. This applies in particular to duplication, translation, microfilming and storage and processing in electronic systems.

heimatec GmbH reserves the right to make technical changes at any time without giving prior notice. This applies in particular to adjustments at any time to meet new or changed international standards, or in case of further developments of our products or manufacturing processes.


The current version of our General Terms and Conditions can be found on our website.

Part-#	Name	
8 010 46 182	Axial drilling and milling head ER 32 AX UT	
	Weight [kg]:	3.270
	Tool drive:	Coupling
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	For hybrid VB24 turret
8 010 46 183	Axial drilling and milling head ER 32 AX UT IC	
	Weight [kg]:	3.300
	Tool drive:	Coupling
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	25
	Please note:	For hybrid VB24 turret
8 013 44 006	Axial drilling and milling head ER 16 AX UT	
	Weight [kg]:	2.280
	Tool drive:	Coupling
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 16 A - u-tec
	Gear ratio [i]:	1:4
	Torque max [Nm]:	5
	Rotation max [1/min]:	24000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	For hybrid VB24 turret
8 019 45 078	Axial drilling and milling head ER 25	
	Weight [kg]:	8.060
	Notation:	offset
	Employment for:	Main spindle
	Version:	left
	Tool drive:	Coupling
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 25
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
	Offset [mm]:	95

Part-#	Name	
8 019 45 123	Axial drilling and milling head ER 25 AX UT	
	Weight [kg]:	7.220
	Notation:	offset
	Version:	left
	Tool drive:	Coupling
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 25 A - u-tec
	Gear ratio [i]:	1:3
	Torque max [Nm]:	16
	Rotation max [1/min]:	15000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	stronger bearing
	Offset [mm]:	50
8 019 45 155	Axial drilling and milling head ER 25 AX UT IC	
	Weight [kg]:	7.300
	Notation:	offset
	Version:	left
	Tool drive:	Coupling
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 25 A - u-tec
	Gear ratio [i]:	1:3
	Torque max [Nm]:	16
	Rotation max [1/min]:	15000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Please note:	stronger bearing
	Offset [mm]:	50
8 019 46 095	Axial drilling and milling head ER 32 AX UT	
	Weight [kg]:	7.210
	Notation:	offset
	Version:	left
	Tool drive:	Coupling
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	1:2
	Torque max [Nm]:	25
	Rotation max [1/min]:	12000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	stronger bearing
	Offset [mm]:	50
8 019 46 163	Axial drilling and milling head ER 32 AX UT IC	
	Weight [kg]:	7.280
	Notation:	offset
	Version:	left
	Tool drive:	Coupling
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	1:2

Part-#	Name	
	Torque max [Nm]:	25
	Rotation max [1/min]:	12000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Please note:	stronger bearing
	Offset [mm]:	50
8 019 46 220	Axial drilling and milling head ER 32 AX UT	
	Weight [kg]:	8.000
	Notation:	offset
	Version:	left
	Tool drive:	Coupling
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	stronger bearing
	Offset [mm]:	50
8 030 44 076	Radial drilling and milling head ER 16 AX UT	
	Weight [kg]:	6.400
	Version:	left
	Tool drive:	Coupling
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 16 A - u-tec
	Gear ratio [i]:	1:4
	Torque max [Nm]:	5
	Rotation max [1/min]:	24000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	for hybrid VB 24 turret
	Center distance [mm]:	85
8 030 46 325	Radial drilling and milling head ER 32 AX UT	
	Weight [kg]:	5.890
	Version:	left
	Tool drive:	Coupling
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	50
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Please note:	for hybrid VB 24 turret
	Center distance [mm]:	85

Part-#	Name
8 030 46 326	Radial drilling and milling head ER 32 AX UT IC
	Weight [kg]: 6.470
	Version: left
	Tool drive: Coupling
	Shank size [mm]: 40.00
	Shank type: VDI
	Tool adaption: ER 32 A - u-tec
	Gear ratio [i]: 1:1
	Torque max [Nm]: 50
	Rotation max [1/min]: 6000
	Rotating direction: opposite
	Coolant: IC/Ext
	Pressure max [bar]: 140
	Please note: for hybrid VB 24 turret
	Center distance [mm]: 85
8 030 46 438	Radial drilling and milling head ER 32 AX UT
	Weight [kg]: 6.040
	Version: left
	Tool drive: Coupling
	Shank size [mm]: 40.00
	Shank type: VDI
	Tool adaption: ER 32 A - u-tec
	Gear ratio [i]: 1:1
	Torque max [Nm]: 50
	Rotation max [1/min]: 6000
	Rotating direction: same
	Coolant: EXT
	Please note: stronger bearing
	Center distance [mm]: 85
8 040 44 082	Universal head $\pm 90^\circ$ adjustable ER 16 AX UT
	Version: left
	Tool drive: Coupling
	Shank size [mm]: 40.00
	Shank type: VDI
	Tool adaption: ER 16 A - u-tec
	Gear ratio [i]: 1:1
	Torque max [Nm]: 25
	Rotation max [1/min]: 6000
	Rotating direction: opposite
	Coolant: EXT
	Center distance [mm]: 87
8 040 44 084	Universal head $\pm 90^\circ$ adjustable ER 16 AX UT IC
	Version: left
	Tool drive: Coupling
	Shank size [mm]: 40.00
	Shank type: VDI
	Tool adaption: ER 16 A - u-tec
	Gear ratio [i]: 1:1
	Torque max [Nm]: 25
	Rotation max [1/min]: 6000
	Rotating direction: opposite
	Coolant: IC/Ext
	Pressure max [bar]: 140
	Center distance [mm]: 87

Part-#	Name	
8 040 44 086	Universal head $\pm 90^\circ$ adjustable ER 16 AX UT	
	Weight [kg]:	5.260
	Version:	left
	Tool drive:	Coupling
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 16 A - u-tec
	Gear ratio [i]:	1:2
	Torque max [Nm]:	12
	Rotation max [1/min]:	12000
	Rotating direction:	opposite
	Coolant:	EXT
	Center distance [mm]:	87
8 040 44 088	Universal head $\pm 90^\circ$ adjustable ER 16 AX UT IC	
	Version:	left
	Tool drive:	Coupling
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 16 A - u-tec
	Gear ratio [i]:	1:2
	Torque max [Nm]:	12
	Rotation max [1/min]:	12000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Center distance [mm]:	87
8 040 45 040	Universal head $\pm 90^\circ$ adjustable ER 25 AX UT	
	Weight [kg]:	5.490
	Version:	left
	Tool drive:	Coupling
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 25 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Center distance [mm]:	87
8 040 45 075	Universal head $\pm 90^\circ$ adjustable ER 25 AX UT IC	
	Weight [kg]:	5.500
	Version:	left
	Tool drive:	Coupling
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 25 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Center distance [mm]:	87

Part-#	Name	
8 043 45 006	Universal head ± 90° adjustable ER 25 AX UT	
	Weight [kg]:	8.090
	Notation:	offset
	Employment for:	Haas VB 24 turret
	Version:	left
	Tool drive:	Coupling
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 25 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
	Please note:	stronger bearing
	Center distance [mm]:	85
	Offset [mm]:	99
8 043 45 007	Universal head ± 90° adjustable ER 25 AX UT IC	
	Notation:	offset
	Employment for:	Haas VB 24 turret
	Version:	left
	Tool drive:	Coupling
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 25 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	25
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	IC/Ext
	Pressure max [bar]:	140
	Please note:	stronger bearing
	Center distance [mm]:	85
	Offset [mm]:	99
8 210 46 018	Tool holder E4-40xER 32	
	Weight [kg]:	1.380
	Shank size [mm]:	40.00
	Shank type:	VDI
	Tool adaption:	ER 32
	Coolant:	IC
	Please note:	For hybrid VB24 turret
8 224 03 006	Cut-off holder SH 32	
	Weight [kg]:	2.090
	Notation:	180° reversible
	Version:	short
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Clampshaft SH 32
	Coolant:	EXT

Part-#	Name	
8 224 03 007	Cut-off holder SH 32	
	Weight [kg]:	2.090
	Notation:	180° reversible
	Version:	long
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Clampshaft SH 32
	Coolant:	EXT
8 224 03 012	Cut-off holder SH 32	
	Weight [kg]:	2.160
	Notation:	180° reversible
	Version:	Clampshaft on turret center
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Clampshaft SH 32
	Coolant:	EXT
8 224 04 006	Universal turning holder sq. 19,05 (0,75")	
	Weight [kg]:	1.710
	Shank type:	VDI
	Machine adaption:	Centering key b 12 (0,437")
	Tool adaption:	Sq. 3/4" (19,05mm)
	Coolant:	EXT
8 224 04 009	Cut-off/turning holder sq. 19,05 (0,75")	
	Weight [kg]:	1.930
	Notation:	180° reversible
	Version:	short
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Sq. 3/4" (19,05mm)
	Coolant:	EXT
8 224 04 010	Universal turning holder sq. 20	
	Weight [kg]:	1.680
	Shank type:	BMT
	Machine adaption:	Centering key b 12 (0,437")
	Tool adaption:	Sq. 20
	Coolant:	EXT
8 224 04 011	Cut-off/turning holder sq. 20	
	Weight [kg]:	1.900
	Version:	short
	Shank type:	VDI
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Sq. 20
	Coolant:	EXT
8 224 04 013	Cut-off/turning holder sq. 19,05 (0,75")	
	Weight [kg]:	3.070
	Notation:	180° reversible
	Version:	long
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Sq. 3/4" (19,05mm)
	Coolant:	EXT

Part-#	Name	
8 224 04 014	Cut-off/turning holder sq. 20	
	Weight [kg]:	3.030
	Notation:	180° reversible
	Version:	long
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Sq. 20
	Coolant:	EXT
8 224 04 024	Universal turning holder sq. 19,05 (0,75")	
	Weight [kg]:	3.970
	Shank type:	HYB
	Machine adaption:	Centering key b 12 (0,437")
	Tool adaption:	Sq. 3/4" (19,05mm)
	Coolant:	EXT
8 224 04 033	Universal turning holder sq. 20	
	Weight [kg]:	3.900
	Shank type:	HYB
	Machine adaption:	Centering key b 12 (0,437")
	Tool adaption:	Sq. 20
	Coolant:	EXT
8 224 04 041	Cut-off/turning holder sq. 19,05 (0,75")	
	Notation:	180° reversible
	Version:	long; clampshaft on turret center
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Sq. 3/4" (19,05mm)
	Coolant:	EXT
8 240 07 006	Boring bar holder Ø 25,4 (1")	
	Weight [kg]:	2.280
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Ø 1" (25,4mm)
	Coolant:	IC/Ext
	Center distance [mm]:	25,4 (1")
8 240 07 007	Boring bar holder Ø 25	
	Weight [kg]:	2.290
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Ø 25
	Coolant:	IC/Ext
	Center distance [mm]:	25,4 (1")
8 240 08 005	Boring bar holder Ø 31,75 (1,25")	
	Weight [kg]:	2.090
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Ø 1 1/4" (31,75mm)
	Coolant:	IC/Ext
	Center distance [mm]:	25,4 (1")

Part-#	Name	
8 240 08 011	Boring bar holder Ø 32	
	Weight [kg]:	2.090
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Ø 32
	Coolant:	IC/Ext
	Center distance [mm]:	25,4 (1")
8 240 09 016	Boring bar holder Ø 38,10 (1,5")	
	Weight [kg]:	3.390
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Ø 1 1/2" (38,1mm)
	Coolant:	IC/Ext
	Center distance [mm]:	38,1(1,5")
8 240 09 023	Boring bar holder Ø 44,45 (1,75")	
	Weight [kg]:	3.150
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Ø 1 3/4" (44,45mm)
	Coolant:	IC/Ext
	Center distance [mm]:	38,1(1,5")
8 240 09 024	Boring bar holder Ø 40	
	Weight [kg]:	3.360
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Ø 40
	Coolant:	IC/Ext
	Center distance [mm]:	38,1(1,5")
8 240 09 026	Boring bar holder Ø 50,8 (2")	
	Weight [kg]:	2.900
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Ø 2" (50,8mm)
	Coolant:	IC/Ext
	Center distance [mm]:	38,1(1,5")
8 244 04 002	Combi facing holder sq. 3/4"	
	Weight [kg]:	1.880
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Sq. 3/4" (19,05mm)
	Coolant:	EXT

Part-#	Name	
8 244 04 004	Combi facing holder sq. 20	
	Weight [kg]:	1.840
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Sq. 20
	Coolant:	EXT
8 251 04 006	Double turning holder sq. 19,05 (0,75")	
	Weight [kg]:	5.160
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Sq. 3/4" (19,05mm)
	Coolant:	EXT
8 251 04 007	Double turning holder sq. 20	
	Weight [kg]:	5.060
	Notation:	180° reversible
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Sq. 20
	Coolant:	EXT
8 251 04 018	Combi multiple holder sq. 3/4"	
	Weight [kg]:	5.050
	Notation:	Y-axes offset; 180° reversible
	Version:	Special
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Sq. 3/4" (19,05mm)
		Sq. 3/4" (19,05mm)
	Coolant:	EXT
8 253 06 000	Double boring bar holder Ø 19,05 (0,75")	
	Weight [kg]:	2.410
	Notation:	180° reversible
	Version:	short
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Ø 3/4" (19,05mm)
	Coolant:	IC/Ext
	Please note:	Center [mm] 31,75(1,25")/86,36(3,4")
8 253 06 001	Double boring bar holder Ø 20	
	Weight [kg]:	2.400
	Notation:	180° reversible
	Version:	short
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Ø 20
	Coolant:	IC/Ext
	Please note:	Center [mm] 31,75(1,25")/86,36(3,4")

Part-#	Name	
8 253 06 002	Double boring bar holder Ø 19,05 (0,75")	
	Weight [kg]:	3.000
	Notation:	180° reversible
	Version:	long
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Ø 3/4" (19,05mm)
	Coolant:	IC/Ext
	Please note:	Center [mm] 60,32(2,375")/114,935(4,525")
8 253 06 003	Multiple boring bar holder Ø 20	
	Weight [kg]:	3.000
	Notation:	180° reversible
	Version:	long
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Ø 20
	Coolant:	IC/Ext
	Please note:	Center [mm] 60,32(2,375")/114,935(4,525")
8 253 07 009	Double boring bar holder Ø 25	
	Weight [kg]:	4.300
	Notation:	180° reversible
	Version:	long, special
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Ø 25
	Coolant:	IC/Ext
	Please note:	Center [mm]:60,325/112,935
8 253 07 010	Double boring bar holder Ø 25,4 (1")	
	Notation:	180° reversible
	Version:	long, special
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Ø 1" (25,4mm)
	Coolant:	IC/Ext
	Please note:	Center [mm]:60,325/112,935
8 253 07 037	Double boring bar holder Ø 31,75 (1,25")	
	Notation:	180° reversible
	Version:	long, special
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Ø 1 1/4" (31,75mm)
	Coolant:	IC/Ext
	Please note:	Center [mm]:60,325/112,935
8 253 08 004	Double boring bar holder Ø 32	
	Weight [kg]:	4.030
	Notation:	180° reversible
	Version:	long, special
	Shank type:	BMT
	Machine adaption:	Centering key slot b 15 (0,591")
	Tool adaption:	Ø 32
	Coolant:	IC/Ext
	Please note:	Center [mm]:60,325/112,935

HAAS

ST-30SS/SSY - Hybrid VB 24

heimatec®

Part-#	Name
8 259 02 002	Combi multiple holder 2x sq. 20
	Weight [kg]: 5.080
	Notation: Y-axes offset
	Shank type: HYB
	Machine adaption: Centering key slot b 15
	Tool adaption: Sq. 20
	Sq. 20
	Coolant: EXT

heimatec.u-tec®

heimatec.com

Products / Tool change systems /
u-tec® Tool-changing system



versions see catalog



heimatec.easy-quick

heimatec.com

Products / Tool change systems /
easy-quick HT quick-changing system



versions see catalog



heimatec.Capto™

heimatec.com

Products / Tool change systems /
heimatec.Capto™ quick-changing system



versions see catalog



heimatec.accessories

heimatec.com

Products / Accessories



versions see catalog





● heimatec overseas branches

○ global representations of heimatec

heimatec[®]

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
77871 Renchen
Germany

T +49 7843 9466 0
www.heimatec.com
info@heimatec.com

Please find the contact details of our worldwide trading partners on our website:
<https://heimatec.com/business-partners>