

Gildemeister  
**CTX 200 E V5**



# High-tech from heimatec - heimatec - Tools and systems for productive turning and milling

heimatec belongs to the international technology and quality leaders for precision tools and specializes in the development and production of high-precision static and live tools for all CNC lathes, CNC turn-/mill machines and CNC machining centers.

The range of products\* spans from static BMT and VDI tool holders, live tools up to highly complex customer-specific individual solutions. heimatec, headquartered in Renchen, has a own subsidiary in Asia and India and numerous representatives as well as trading partners all over the world.

## \*OUR PRODCUTS

Static tool holders

Live tool units

Precision tools

Tools for turning and machining centres

Tools for swiss type lathes

Tool changing and uick-change systems



Tool systems for gear production

Digital tool management

This catalogue, including all its parts, is protected by copyright. Any use outside the restricted limitations of the Copyright Act without the consent of heimatec is inadmissible and liable to prosecution. This applies in particular to duplication, translation, microfilming and storage and processing in electronic systems.

**heimatec GmbH** reserves the right to make technical changes at any time without giving prior notice. This applies in particular to adjustments at any time to meet new or changed international standards, or in case of further developments of our products or manufacturing processes.

The current version of our General Terms and Conditions can be found on our website.

Part-#	Name	
<b>8 010 14 019</b>	<b>Axial drilling and milling head ER 20 AX UT</b>	
	Weight [kg]:	1.150
	Tool drive:	DIN 5480
	Shank size [mm]:	20.00
	Shank type:	VDI
	Tool adaption:	ER 20 A - u-tec
	Gear ratio [i]:	1:1
	Torque max [Nm]:	16
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
<b>8 010 14 023</b>	<b>Axial drilling and milling head ER 20 IC air</b>	
	Tool drive:	DIN 5480
	Shank size [mm]:	20.00
	Shank type:	VDI
	Tool adaption:	ER 20
	Gear ratio [i]:	1:1
	Torque max [Nm]:	16
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	IC air
	Pressure max [bar]:	10
<b>8 011 14 006</b>	<b>Axial milling head universal arbor 16</b>	
	Weight [kg]:	1.600
	Tool drive:	DIN 5480
	Shank size [mm]:	20.00
	Shank type:	VDI
	Tool adaption:	Universal arbor 16
	Gear ratio [i]:	1:1
	Torque max [Nm]:	16
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	EXT
<b>8 013 14 000</b>	<b>Axial drilling and milling head ER 16 AX</b>	
	Weight [kg]:	2.300
	Tool drive:	DIN 5480
	Shank size [mm]:	20.00
	Shank type:	VDI
	Tool adaption:	ER 16 A
	Gear ratio [i]:	1:2
	Torque max [Nm]:	6
	Rotation max [1/min]:	12000
	Rotating direction:	same
	Coolant:	EXT
<b>8 030 14 022</b>	<b>Radial drilling and milling head ER 20</b>	
	Weight [kg]:	1.920
	Version:	left
	Tool drive:	DIN 5480
	Shank size [mm]:	20.00
	Shank type:	VDI
	Tool adaption:	ER 20
	Gear ratio [i]:	1:1
	Torque max [Nm]:	10

Part-#	Name	
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Center distance [mm]:	75
<b>8 030 14 024</b>	<b>Radial drilling and milling head ER 20 IC</b>	
	Employment for:	Main spindle
	Version:	left
	Tool drive:	DIN 5480
	Shank size [mm]:	20.00
	Shank type:	VDI
	Tool adaption:	ER 20
	Gear ratio [i]:	1:1
	Torque max [Nm]:	10
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Center distance [mm]:	75
<b>8 030 14 026</b>	<b>Radial drilling and milling head ER 20</b>	
	Version:	left
	Tool drive:	DIN 5480
	Shank size [mm]:	20.00
	Shank type:	VDI
	Tool adaption:	ER 20
	Gear ratio [i]:	1:2
	Torque max [Nm]:	6,5
	Rotation max [1/min]:	12000
	Rotating direction:	opposite
	Coolant:	EXT
	Center distance [mm]:	75
<b>8 030 14 028</b>	<b>Radial drilling and milling head ER 20 IC</b>	
	Version:	left
	Tool drive:	DIN 5480
	Shank size [mm]:	20.00
	Shank type:	VDI
	Tool adaption:	ER 20
	Gear ratio [i]:	1:2
	Torque max [Nm]:	6,5
	Rotation max [1/min]:	12000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Center distance [mm]:	75
<b>8 030 14 030</b>	<b>Radial drilling and milling head ER 16 AX</b>	
	Weight [kg]:	2.160
	Version:	left
	Tool drive:	DIN 5480
	Shank size [mm]:	20.00
	Shank type:	VDI
	Tool adaption:	ER 16 A
	Gear ratio [i]:	1:3
	Torque max [Nm]:	4
	Rotation max [1/min]:	18000
	Rotating direction:	opposite
	Coolant:	EXT
	Center distance [mm]:	75

Part-#	Name	
<b>8 030 14 032</b>	<b>Radial drilling and milling head ER 16 AX IC</b>	
	Version:	left
	Tool drive:	DIN 5480
	Shank size [mm]:	20.00
	Shank type:	VDI
	Tool adaption:	ER 16 A
	Gear ratio [i]:	1:3
	Torque max [Nm]:	4
	Rotation max [1/min]:	18000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Center distance [mm]:	75
<b>8 030 14 034</b>	<b>Radial drilling and milling head ER 20 IC</b>	
	Employment for:	Sub spindle
	Tool drive:	DIN 5480
	Shank size [mm]:	20.00
	Shank type:	VDI
	Tool adaption:	ER 20
	Gear ratio [i]:	1:1
	Torque max [Nm]:	10
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	IC/Ext
	Center distance [mm]:	75
<b>8 030 14 039</b>	<b>Radial drilling and milling head ER 16</b>	
	Version:	left
	Tool drive:	DIN 5480
	Shank size [mm]:	20.00
	Shank type:	VDI
	Tool adaption:	ER 16
	Gear ratio [i]:	1:1
	Torque max [Nm]:	10
	Rotation max [1/min]:	6000
	Rotating direction:	opposite
	Coolant:	EXT
	Center distance [mm]:	75
<b>8 033 14 020</b>	<b>Radial drilling and milling head ER 20 IC</b>	
	Version:	Left
	Tool drive:	DIN 5480
	Shank size [mm]:	20.00
	Shank type:	VDI
	Tool adaption:	ER 20
	Gear ratio [i]:	1:1
	Torque max [Nm]:	10
	Rotation max [1/min]:	6000
	Rotating direction:	same
	Coolant:	IC/Ext
<b>8 039 14 004</b>	<b>Radial drilling and milling head ER 20</b>	
	Weight [kg]:	2.280
	Version:	double spindle
	Tool drive:	DIN 5480
	Shank size [mm]:	20.00
	Shank type:	VDI
	Tool adaption:	ER 20

Gildemeister  
CTX 200 E V5



Part-#	Name
--------	------

Gear ratio [i]:	1:1
Torque max [Nm]:	10
Rotation max [1/min]:	6000
Rotating direction:	same
Coolant:	EXT
Center distance [mm]:	75

## heimatec.u-tec®

heimatec.com

Products / Tool change systems /  
u-tec® Tool-changing system



versions see catalog



## heimatec.easy-quick

heimatec.com

Products / Tool change systems /  
easy-quick HT quick-changing system



versions see catalog



## heimatec.Capto™

heimatec.com

Products / Tool change systems /  
heimatec.Capto™ quick-changing system



versions see catalog



## heimatec.accessories

heimatec.com

Products / Accessories



versions see catalog





● heimatec overseas branches

○ global representations of heimatec

**heimatec**<sup>®</sup>

**heimatec GmbH**  
Präzisionswerkzeuge  
Carl-Benz-Str. 4  
77871 Renchen  
Germany

T +49 7843 9466 0  
[www.heimatec.com](http://www.heimatec.com)  
[info@heimatec.com](mailto:info@heimatec.com)

Please find the contact details of our worldwide trading partners on our website:  
<https://heimatec.com/business-partners>