

TOPSELLER -
many more available!

Live Tools


heimatec®

Miyano


BNE 51 MSY

Part-#	Tool adaption	Rotation max [1/min]	Gear ratio	Coolant	Pressure max.	Center distance
Axial drilling and milling head						
8 010 45 224	ER 25 A - u-tec	15.000	1:1	EXT	--	--
8 010 45 225	ER 25 A - u-tec	12.000	1:1	IC/Ext	100 bar	--
Radial drilling and milling head						
8 030 45 136	ER 25 A - u-tec	12.000	1:1	IC/Ext	140 bar	65 mm
8 030 45 169	ER 25 A - u-tec	12.000	1:1	EXT	--	65 mm
Radial drilling and milling head, double spindle						
8 039 45 106	ER 25 A - u-tec	12.000	1:1	EXT	--	--
8 039 45 076	ER 25 A - u-tec	12.000	1:1	EXT	--	65 mm
Universal head, offset						
8 043 44 005	ER 16 A - u-tec	6.000	1:1	EXT	--	50 mm
8 043 45 000	ER 25 A - u-tec	6.000	1:1	EXT	--	50 mm
Multispindle drilling head						
8 050 44 005	ER 16 A - u-tec	12.000	1:1	EXT	--	--


Illustrations similar.




8 010 45 224



8 030 45 136



8 039 45 106



8 043 44 005



8 050 44 005

TOPSELLER -
many more available!

Static Tools

heimatec®

Miyano

BNE 51 MSY

Part-#	Tool adaption	Coolant	Pressure max.	Center distance
Universal turning holder				
8 224 04 000	Sq. 20	EXT	--	--
8 224 04 068	Sq. 20	IC/Ext	100 bar	--
Boring bar holder				
8 240 08 000	Ø 32	IC/Ext	--	75 mm
8 240 09 002	Ø 40	IC/Ext	--	75 mm
Double boring bar holder				
8 253 07 000	Ø 25	IC/Ext	--	--

Illustrations similar.



8 224 04 000



8 224 04 068



8 240 08 000



8 253 07 000