

Biglia

B 501 Y/SY -

Klauenkupplung



High-tech from heimatec - heimatec - Tools and systems for productive turning and milling

heimatec belongs to the international technology and quality leaders for precision tools and specializes in the development and production of high-precision static and live tools for all CNC lathes, CNC turn-/mill machines and CNC machining centers.

The range of products* spans from static BMT and VDI tool holders, live tools up to highly complex customer-specific individual solutions. heimatec, headquartered in Renchen, has a own subsidiary in Asia and India and numerous representatives as well as trading partners all over the world.

***OUR PRODCUTS**

Static tool holders

Live tool units

Precision tools

Tools for turning and machining centres

Tools for swiss type lathes

Tool changing and uick-change systems

Tool systems for gear production

Digital tool management

This catalogue, including all its parts, is protected by copyright. Any use outside the restricted limitations of the Copyright Act without the consent of heimatec is inadmissible and liable to prosecution. This applies in particular to duplication, translation, microfilming and storage and processing in electronic systems.

heimatec GmbH reserves the right to make technical changes at any time without giving prior notice. This applies in particular to adjustments at any time to meet new or changed international standards, or in case of further developments of our products or manufacturing processes.

The current version of our General Terms and Conditions can be found on our website.

Part-#	Name
8 019 55 000	Axial drilling and milling head ER 25
	Weight [kg]: 5.360
	Tool drive: Coupling
	Shank size [mm]: 55.00
	Shank type: BMT
	Tool adaption: ER 25
	Gear ratio [i]: 1:2
	Torque max [Nm]: 25
	Rotation max [1/min]: 10000
	Rotating direction: opposite
	Coolant: EXT
8 039 56 002	Radial drilling and milling head ER 32AX/ 25AX
	Weight [kg]: 9.780
	Version: double spindle
	Tool drive: Coupling
	Shank size [mm]: 55.00
	Shank type: BMT
	Tool adaption: ER 32 A
	ER 25 A
	Gear ratio [i]: 1:1
	Torque max [Nm]: 50
	Rotation max [1/min]: 6000
	Rotating direction: same
	Coolant: EXT
	Center distance [mm]: 85
8 040 54 003	Universal head $\pm 90^\circ$ adjustable ER 16
	Tool drive: Coupling
	Shank size [mm]: 55.00
	Shank type: BMT
	Tool adaption: ER 16
	Gear ratio [i]: 1:1
	Torque max [Nm]: 10
	Rotation max [1/min]: 5000
	Rotating direction: same
	Coolant: EXT



● heimatec overseas branches

○ global representations of heimatec

heimatec[®]

heimatec GmbH
Präzisionswerkzeuge
Carl-Benz-Str. 4
77871 Renchen
Germany

T +49 7843 9466 0
www.heimatec.com
info@heimatec.com

Please find the contact details of our worldwide trading partners on our website:
<https://heimatec.com/business-partners>